



S3592BTRM
Tub/Shower Trim
Specification Submittal

Location:

Model Numbers

- S3592BTRM**
Tub/Shower System Trim

Valve Options:

- S262 Series Temptrol Shower Valve with TRM modifier
- S162 Series Temptrol Shower Valve requires TC modifier

Feature Highlights

- Dia Tub/Shower Trim.
- Requires Temptrol® Pressure Balancing Tub/Shower Valve.
- Integral diverter control.
- Metal lever handle.
- 7" slip-on tub spout.
- 7 mode showerhead.
- 2.0 gpm (9.5 L/min) flow restrictor.
- Components shall be metal and nonmetal construction, plated in standard polished chrome finish.

Options/Modifications

- 15** 1.5 gpm (5.7 L/min) flow restrictor
- 175** 1.75 gpm (6.6 L/min) flow rate restrictor
- Delete Suffix B** Chrome plastic escutcheon on valve with color graphic/indicators in place of standard brass escutcheon
- L1** Less showerhead
- L4** Less head, arm, and flange
- L7** Less handle
- BBZ** Brushed Bronze finish
- MB** Matte Black finish
- STN** Satin Nickel finish
- TC** Test Cap Trim (includes TA-10&T-12A) *used with S162 series Temptrol Shower Valve*

Compliance

- ASME A112.18.1/CSA B125.1
- WaterSense 1.5 gpm (5.7 L/min) 1.75 gpm (6.6 L/min) 2.0 gpm (7.6 L/min)
- Lever meets ADA requirements for operation.



Warranty

Limited Lifetime - to the original end purchaser in consumer/residential installations.
10 Years - for commercial/industrial installations. Refer to www.symmons.com/warranty for complete warranty information.



SKU Builder


Series	Finish	Modifier	Flow Rate	TRM (required)	TC	Final SKU
3592B	STN		15	TRM		3592BSTN15TRM
3592	MB	L1		TRM	TC	3592MBL1TRMTC

Note: No more than two modifiers (L1-L7) and modifier order will follow numerical order.

Architectural/ Engineering Specification

Symmons Dia Tub and Shower Trim _____ Includes Dia Tub and Shower Trim powered by Temptrol® Pressure Balancing Shower Valve. Features integral diverter control, metal lever handle, 7" non-diverter tub spout, single mode showerhead, 2.0 gpm (7.6 L/min) flow restrictor, Components shall be metal and nonmetal construction, plated in standard polished chrome finish. 10 Year Commercial Warranty. ASME A112.18.1/CSA B125.1, WaterSense 1.5 gpm (5.7 L/min), 1.75 gpm (6.6 L/min), 2.0 gpm (7.6 L/min) compliant. Lever handle meets ADA requirements for operation. Available options: "15 - 1.5 gpm (5.7 L/min) flow restrictor", "175 - 1.75 gpm (6.6 L/min) flow rate restrictor", "Delete Suffix B - Chrome plastic escutcheon", "L1 - Less showerhead", "L4 - Less showerhead, arm, and flange", "L7 - Less handle", "TC - Test Cap Trim", "BBZ - Brushed Bronze finish", "MB - Matte Black finish", and "STN - Satin Nickel finish".

Dimensions



Notes:

- 1) Valve body and piping not included and shown as reference only.
- 2) Plaster shield (p/n T-176) for dry wall, plaster or other type walls 1/2" or greater.
- 3) All dimensions measured from nominal rough-in.
- 4) Dimensions subject to change without notice.