

9713

INSTALLATION INSTRUCTIONS

Please read carefully and save these instructions, as you may need them at a later date.

CAUTION

Turn off the main power at the circuit breaker before installing the fixture, in order to prevent possible shock.

GENERAL

All electrical connections must be in accordance with local and National Electrical Code (N.E.C) standards. If you are unfamiliar with proper electrical wiring connections, obtain the services of a qualified electrician.

Remove the fixture and the mounting package from the box and make sure that no parts are missing by referencing the illustrations on the installation instructions.

ASSEMBLY AND INSTALLATION

1. Attach the Round mounting bar to the OUTLET BOX by the two box screws
2. Pull out the wires and ground wire from the Outlet Box
Make wire connections with wire nut
---WHITE WIRE from fixture to WHITE WIRE from power source.
---BLACK WIRE from fixture to BLACK WIRE from power source.
---Loop the GROUND WIRE to Round mounting bar with a GREEN SCREW.
3. Place the Canopy over the OUTLET BOX through the two MACHINE SCREWS
Secure it with two Ball NUT.
4. Installing bulbs (Bulbs not included)
(Please don't exceed the maximum capacity that recommended on the package).
5. Place GLASS to the SOCKET ASSEMBLY, securing it with DECORATIVE SCREWS.

INSTALLATION IS NOW COMPLETED.

