

Consistent Set Times Allow for Same-Day Finishing



30% lighter than standard setting compound.

APPROXIMATE WORKING TIME VERSUS SET/HARDENING TIME

Quick Set Lite	Working Time (Minutes)	Set/Hardening Time (Minutes)
5	3–5	10–20
20	15–20	20–40
45	35–45	45–70
90	70–90	90–125
210	180–210	210–280

For more information on mixing and estimated working times, go to the FAQ section at proformfinishing.com.



National Gypsum Company is the exclusive service provider for products manufactured by ProForm Finishing Products, LLC.
ProForm® Quick Set Lite™ Setting Compound is manufactured by ProForm Finishing Products, LLC.

ProForm Quick Set Lite Setting Compounds are quick-setting (hardening) compounds that are mold resistant and are not affected by humidity once they have set and dried. Quick Set Lite provides a lightweight, easy-to-sand finish for fast, smooth joint finishing. It is specially formulated to provide excellent joint strength, even in poor drying conditions.

Quick Set Lite permits heavy fills and faster joint finishing with low shrinkage. It is compatible with all types of gypsum board and may be used where a shortened joint finishing schedule is desired. It can be used as a prefill material for gaps in gypsum board construction that are wider than recommended and in voids in above-grade interior concrete.

These products are mold resistant and have achieved GREENGUARD Gold Certification for low chemical emissions into indoor air during product usage.

ADVANTAGES

- Quick and easy mixing and sanding.
- 30% lighter than standard setting compounds.
- Consistent work/set time.
- Streamlines scheduling; recoat immediately once previous coat dries and finish same day.
- Mold resistant.
- Not affected by humidity or moisture when hardened and dried.
- Reduces joint deformities such as ridging and beading.
- Available in 5, 20, 45, 90 and 210 minute set times for flexibility.

SPECIFICATIONS

Packaging: Bag	18 lbs. (8.2 kg)
Approximate Coverage	1 bag covers 325 sq ft



PROFORM®
Finishing Products

proformfinishing.com