## Tools Needed:

Implementos necesarios:



## **DOUBLE DOOR**

## HARDWARE REPAIR KIT

- 1. Remove door by lifting door up and tilting outward.
- 2. Remove existing hardware.
- 3. Install new hardware.
- 4. Re-install door by inserting top pivot pin and quide roller into bracket and track first, then insert bottom pivot pin into bracket.
- 5. If necessary, adjust vertical and horizontal alignment using bottom pivot.

## KIT DE REPARACIÓN DE LOS HERRAIES DE UNA PUERTA DOBLE

- 1. Desmonte la puerta alzándola e inclinándola hacia afuera.
- 2. Retire los herrajes existentes.
- 3. Instale los herrajes nuevos.
- 4. Vuelva a instalar la puerta insertando el pasador pivotante superior y el rodillo quía en el soporte y el primer riel, luego inserte el pasador pivotante inferior en el soporte.
- 5. Si es necesario, ajuste la alineación vertical y horizontal utilizando el pivotante inferior.



For warranty info visit mdbuildingproducts.com

Para obtener información sobre la garantía, visite mdbuildingproducts.com



Top Pivot Pin Bracket



Top Guide Roller



Door Snugger



Top Pivot Pin



Door Aligner



Bottom Jamb Bracket



Made in China. Hecho en China. M-D Building Products, Inc. Oklahoma City, OK 73118 Rev 07/24 mdteam.com

**△WARNING: Cancer and Reproductive Harm** - www.P65Warnings.ca.gov.

ADVERTENCIA: Cáncer v Daño Reproductivo - www.P65Warnings.ca.gov.



OUESTIONS? | PREGUNTAS? MDBUILDINGPRODUCTS.COM







