### 29 137

### **GROHTHERM® SMARTCONTROL**

# Pure Freude an Wasser

# DUAL FUNCTION THERMOSTATIC VALVE TRIM WITH CONTROL MODULE

#### STANDARD SPECIFICATION:

- GROHE StarLight®
- GROHE SmartControl®: push for ON-OFF, turn for volume adjustment from EcoJoy™ to Full Flow, exchangeable symbols
- GROHE TurboStat® compact ¾" cartridge with wax thermo element
- GROHE SafeStop safety button with manual override at 100°F/38°C
- GROHE SafeStop Plus temperature limiter at 115° F/46° C
- Multiple outlets can be run simultaneously
- 6 1/4" Metal wall escutcheon with GROHE QuickFix®
- 3/8" Thin profile escutcheon
- Wall plate is angle adjustable up to 6°
- Optional flow reducer for CALGreen compliance included (Note: Cannot be used for shower systems that include tub spout)
- Built-in check valve with dirt strainer
- Includes icons to customize push buttons: Hand Shower, Showerhead & Bath Filler
- Includes service stops
- Maximum combined flow performance: 7.7gpm (29L/min) @ 43.5psi (3 bar)
- Requires Grohtherm® Rapido® SmartBox (35 601) (sold separately)



#### **PRODUCT FEATURES:**

- GROHE StarLight®
- GROHE TurboStat®
- GROHE QuickFix®
- GROHE SmartControl®
- GROHE SafeStopPlus

#### **CERTIFICATIONS:**

- Massachusetts Plumbing Board Approved
- ASSE 1016
- CSA B125.1
- CSA B125.16
- ASME A112.18.1
- ASME A112.1016

#### **AVAILABLE FINISHES:**

29137000 GROHE StarLight® Chrome

29137A00 Hard Graphite

29137BE0 Polished Nickel InfinityFinish™

29137EN0 Brushed Nickel InfinityFinish™

29137GN0 Brushed Cool Sunrise

NOTE: Install this product according to the installation guide. ADA, CSA compliant when installed to the specific requirements of these regulations.

We reserve the right to make revisions without notice to product specifications. 12-09-2021



## **GROHTHERM® SMARTCONTROL**



# DUAL FUNCTION THERMOSTATIC VALVE TRIM WITH CONTROL MODULE

#### **TECHNICAL DATA:**

Product Height 6-1/4 in

Product Length 1-11/16 in

Product Width 6-1/4 in

