



## **RESIDENTIAL**

## **Automatic Transfer Switches**



## **SPECIFICATIONS**

OVERVIEW	100 A	150 A	200 A	200 A - 10 Year Warranty	
Briggs and Stratton Model	071210	071250	071270	071272	
Limited Warranty	7			10	
Rated AC Voltage (VAC)	120/240 VAC				
Frequency (Hz)	60				
Number of Poles	2				
Phase	Single				
Power Management	Symphony Choice (Model 6907) Compatible				
Operating Ambient	-20° - 120°F (-28° - 49°C)				
Current Rating	100	150	200		
SED Rated	Yes				
Utility Breaker Rating (amp)	100	150	200		
Breaker Withstand Rating	22000				
Enclosure Type	NEMA/UL 3R				
Enclosure Material	Galvannealed Steel				
Coating Color	Stone Gray Texture				
Load Transition Type (Automatic)	Break Before Make				
Controller Type	Basic Relay Logic Board				
Brown-out Protection	Yes				
Outage to Standby Power Time	26 Second				
Utility Voltage Pickup	80%				
Utility Voltage Drop-Out	85%				
Lug Range - Utility	#6 - 1/0	2AWG - 300MCM	2AWG - 300MCM	2AWG - 300MCM	
Lug Range - Generator	14AWG - 1/0	6AWG - 250MCM	6AWG - 250MCM	6AWG - 250MCM	
Lug Range - Load	14AWG - 1/0	6AWG - 250MCM	6AWG - 250MCM	6AWG - 250MCM	





OVERVIEW	100 A	150 A	200 A	200 A - 10 Year Warranty	
Certifications and Compliance					
UL Listed per UL1008 & UL50e			Yes		
cUL			Yes		
544K Specification			Yes		
97K Label Specification	Yes				
Proposition 65 California	Yes				
NFPA 70 2020 Natioinal Electric Code	Yes				
Weights and Dimensions	100 A	150 A	200 A	200 A - 10 Year Warranty	
Assembled Dimensions (Length x Width x Height)	20.0" L x 14.5" W x 7.0" H	30.1" L x 14.5" W x 7.0" H			
Assembled Weight	36 lbs.	49 lbs.			
Packaged Dimensions (Length x Width x Height)	21.0" L x 15.3" W x 8.5" H	31.0" L x 15.3" W x 8.4" H			
Packaged Weight	39 lbs.	52 lbs.			