

STREAMLABS™ SMARTHOME MONITOR

SPECIFICATIONS SHEET



DESCRIPTION

App-enabled Home Water Monitoring & Leak Detection System.

Applications:

- Water Usage Tracking
- Leak Detection
- Submetering
- Sustainability and Water Conservation

SPECIFICATIONS

App Compatibility

iOS 9.0 or later, compatible with iPhone or iPad

Android 6.0 or later, phone or tablet

Compatible Pipe Sizes

3/4", 1" Copper Tube Size (CTS)

Compatible Pipe Types

Copper Type M & L; PEX; CPVC

Universal Power Supply

Input: 100-240VAC~50/60Hz, 0.2A; Output: 5.9V @ 0.6A UL Listed (included)

Water Temperature

min. 40° F (4.4° C) / max. 80° F (26.6° C)

Operating Pressure

max. 232 psi (16 bar) Limited by Pipe

Ambient Temperature

min. 32° F (0° C) / max. 115° F (46.1° C)

Operating Environment

Indoor use only

Network

Wi-Fi 802.11b/g/n, 2.4 GHz



UFMT-1000

LEAK DETECTION SETTINGS

SETTINGS	USER DEFINABLE
Slow Leak	0.25, 0.5, 1.0 GPM for 5, 10, 15, 20, 30, or 60 mins
Major Leak	2.0, 4.0, 6.0 GPM for 2.5, 5, 10, 15, 20, or 30 mins
Away Mode	0.25 GPM for 15 seconds
Ambient Freeze Alerts	Currently set at <40° F for > 5 mins (not user configurable).

**For Copper Type L, leak detection begins at greater than .5 GPM*

LISTINGS AND APPROVALS

FCC/IC

