

DEWALT

20V MAX* COMPACT PRESS SOLUTIONS

CTS » COPPER TUBE SIZE



1/2 in.
DCE210012



3/4 in.
DCE210034



1 in.
DCE210100



1-1/4 in.
DCE210114



DCE210D2K

IPS » IRON PIPE SIZE



1/2 in.
DCE212012



3/4 in.
DCE212034



1 in.
DCE212100



1/2 in.
DCE212012



3/4 in.
DCE212034



1 in.
DCE212100

DCE212K

ACR » AIR CONDITIONING + REFRIGERATION



NIBCO
PressACR



1/4 in.
DCE214014



3/8 in.
DCE214038



1/2 in.
DCE214012



5/8 in.
DCE214058



3/4 in.
DCE214034



7/8 in.
DCE214078



DCE214K



1/4 in.
DCE217014



3/8 in.
DCE217038



1/2 in.
DCE217012



5/8 in.
DCE217058



3/4 in.
DCE217034



7/8 in.
DCE217078



DCE217K

PEX » PEX TUBE



ASTM F1807
PEX



1/2 in.
DCE215012



3/4 in.
DCE215034



1 in.
DCE215100



1-1/4 in.
DCE215114



1-1/2 in.
DCE215112



1/2 in.
DCE216012



3/4 in.
DCE216034



1 in.
DCE216100



1-1/4 in.
DCE216114



1-1/2 in.
DCE216112

PUREFLOW® PEX



DCE210

20V MAX* COMPACT PRESS TOOL

* Maximum initial battery voltage (measured without a workload) is 20 volts. Nominal voltage is 18.

Viega, ProPress and MegaPress® are registered trademarks of Viega Holding GmbH & Co., which has not endorsed or approved this statement of compatibility. Apollo Powerpress® is a registered trademark of Aalberts Integrated Piping Systems Americas, Inc., which has not endorsed or approved this statement of compatibility. Mueller® and Streamline® are registered trademarks of Mueller International, LLC, which has not endorsed or approved this statement of compatibility.

DCE210 20V MAX* COMPACT PRESS JAW + FITTING COMPATIBILITY

DCE210

20V MAX* COMPACT
PRESS TOOL



PIPE STANDARD	PIPE MATERIAL	FITTING BRAND	FITTING SERIES	DCE210 20V MAX* COMPACT PRESS TOOL
CTS	Copper	Viega®	ProPress®	1/2 in. - 1-1/4 in. DEWALT® Compact CTS Press Jaws Model Numbers: DCE210012, DCE210034, DCE210100, DCE210114
		Apollo®	Apollo Press®	
		Nibco®	Nibco® Press	
			Nibco® PressG	
		Mueller® Industries	Streamline® PRS	
	Stainless Steel	Viega®	ProPress® 316	
IPS	Stainless Steel Carbon Steel	Viega®	MegaPress® 304 & 316	1/2 in. - 1 in. DEWALT® Compact IPS Press Jaws Model Numbers: DCE212012, DCE212034, DCE212100
		Viega®	MegaPress®	
			MegaPress® (GAS)	
		Nibco®	BenchPress®	
			BenchPressG® (GAS)	
		Mueller® Industries	Streamline® STL	
			Streamline® STL-G	
ACR	ACR Copper	NIBCO® PressACR®	PressACR®	1/4 in. - 7/8 in. Compact PressACR® Jaws Model Numbers: DCE214014, DCE214038, DCE214012, DCE214058, DCE214034, DCE214078
		Parker Hannifin CONEX BÄNNINGER®	ZoomLock MAX® & >B< MaxiPro®	1/4 in. - 1-1/8 in. DEWALT Compact ZoomLock MAX® ACR Press Jaws Model Numbers: DCE217014, DCE217038, DCE217012, DCE217058, DCE217034, DCE217078, DCE217118
PEX	PEX	Various Manufacturers	ASTM F1807 ASTM F2159	1/2 in. - 1-1/2 in. DEWALT Compact ASTM F1807 PEX Press Jaws Model Numbers: DCE215012, DCE215034, DCE215100, DCE215114, DCE215112
		Viega®	Pureflow® PEX	1/2 in. - 1-1/2 in. DEWALT Compact Pureflow® PEX Pres Jaws Model Numbers: DCE216012, DCE216034, DCE216100, DCE216114, DCE216112

* Maximum initial battery voltage (measured without a workload) is 20 volts. Nominal voltage is 18.

Viega, ProPress and MegaPress® are registered trademarks of Viega Holding GmbH & Co., which has not endorsed or approved this statement of compatibility. Apollo Powerpress® is a registered trademark of Aalberts Integrated Piping Systems Americas, Inc., which has not endorsed or approved this statement of compatibility. Mueller® and Streamline® are registered trademarks of Mueller International, LLC, which has not endorsed or approved this statement of compatibility.



20V MAX* STANDARD PRESS SOLUTIONS

CTS » COPPER TUBE SIZE



1/2 in.
DCE200012



3/4 in.
DCE200034



1 in.
DCE200100



DCE200M2K



1-1/4 in.
DCE200114



1-1/2 in.
DCE200112



2 in.
DCE200200



2-1/2 in.
DCE200212



3 in.
DCE200300



4 in.
DCE200400



Actuator
DCE200A



DCE201K

IPS » IRON PIPE SIZE



1/2 in.
DCE202012



3/4 in.
DCE202034



1 in.
DCE202100



DCE202K



1-1/4 in.
DCE202114



1-1/2 in.
DCE202112



DCE203K1



2 in.
DCE202200



Actuator
DCE200A

DCE200

20V MAX* STANDARD PRESS TOOL

* Maximum initial battery voltage (measured without a workload) is 20 volts. Nominal voltage is 18.

Viega, ProPress and MegaPress® are registered trademarks of Viega Holding GmbH & Co., which has not endorsed or approved this statement of compatibility. Apollo Powerpress® is a registered trademark of Aalberts Integrated Piping Systems Americas, Inc., which has not endorsed or approved this statement of compatibility. Mueller® and Streamline® are registered trademarks of Mueller International, LLC, which has not endorsed or approved this statement of compatibility.

DCE200 20V MAX* STANDARD PRESS JAW + FITTING COMPATIBILITY

DCE200

20V MAX* STANDARD
PRESS TOOL



PIPE STANDARD	PIPE MATERIAL	FITTING BRAND	FITTING SERIES	DCE200 20V MAX* STANDARD PRESS TOOL
CTS	Copper	Viega®	ProPress®	1/2 in. - 4 in. DEWALT Standard CTS Press Jaws and Rings 1/2 in. - 4 in. Ridgid® Standard ProPress® Jaws and XL-C™ Rings 1/2 in. - 2 in. Ridgid® Standard ProPress® Rings 1/2 in. - 4 in. Milwaukee® M18 Press Jaws and Rings
		Apollo®	Apollo Press®	
		Nibco®	Nibco® Press	1/2 in. - 2 in. DEWALT Standard CTS Press Jaws 1/2 in. - 2 in. Ridgid® Standard Press Jaws 1/2 in. - 2 in. Ridgid® Standard ProPress® Rings 1/2 in. - 2 in. Milwaukee® M18 Press Jaws
		Mueller® Industries	Streamline® PRS™	1/2 in. - 4 in. DEWALT Standard CTS Press Jaws and Rings
	Stainless Steel	Viega®	MegaPress® 304 + 316	1/2 in. - 4 in. DEWALT Standard CTS Press Jaws and Rings 1/2 in. - 4 in. Ridgid® Standard ProPress® Jaws and XL-C™ Rings 1/2 in. - 2 in. Ridgid® Standard ProPress® Rings 1/2 in. - 4 in. Milwaukee® M18 Press Jaws and Rings
IPS	Stainless Steel	Viega®	MegaPress® 304 & 316	1/2 in. - 2 in. DEWALT Standard IPS Press Jaws and Rings
	Carbon Steel	Viega®	MegaPress®	1/2 in. - 2 in. DEWALT Standard IPS Press Jaws and Rings 1/2 in. - 2 in. Ridgid® MegaPress® Jaws and Rings 1/2 in. - 2 in. Milwaukee® M18 Black Iron Press Jaws and Rings
		Viega®	MegaPress® G (Gas)	
		Apollo®	PowerPress® Standard	
		Nibco®	BenchPress™	1/2 in. - 2 in. DEWALT Standard IPS Press Jaws and Rings 1/2 in. - 2 in. Ridgid® MegaPress® Jaws and Rings 1/2 in. - 2 in. Milwaukee® M18 Black Iron Press Jaws and Rings
		Nibco®	BenchPress™ G (Gas)	
PEX	PEX	Viega®	PureFlow® PEX	Ridgid® Standard PureFlow® Pex Jaws

* Maximum initial battery voltage (measured without a workload) is 20 volts. Nominal voltage is 18.

Viega, ProPress and MegaPress® are registered trademarks of Viega Holding GmbH & Co., which has not endorsed or approved this statement of compatibility. Apollo Powerpress® is a registered trademark of Aalberts Integrated Piping Systems Americas, Inc., which has not endorsed or approved this statement of compatibility. Mueller® and Streamline® are registered trademarks of Mueller International, LLC, which has not endorsed or approved this statement of compatibility.

DWPRSTLBR