

GenTite RRS

Material Safety Data Sheet

December 13, 2010

Page: 1

SECTION 1: PRODUCT IDENTIFICATION

Product Name:	All Purpose Bonding Adhesive
Chemical Name/Synonym:	None
Chemical Family:	Polychloroprene
24-Hour Emergency Phone:	(800) 424-9300 CHEMTREC
Manufacturer's Name:	GenTite RRS
Manufacturer's Address:	250 West 96 th Street, Indianapolis, IN 46260
NFPA Hazard Rating:	Health 2, Flammability 3, Reactivity 0
HMIS Hazard Rating:	Health 2, Flammability 3, Reactivity 0

SECTION 2: CHEMICAL COMPOSITION

Chemical Name:	Common Name:	CAS #:	% (by wt)	Exposure Limits:
Acetone	Methyl Ketone	67-64-1	6.8	OSHA PEL 1000 ppm ACGIH TLV 500 ppm ACGIH STEL 750 ppm
Petroleum Hydrocarbon Distillates (Primarily Hexane)	Textile Spirits	64741-84-0	33	None Established
Toluene	Toluol	108-88-3	35	OSHA PEL 200 ppm OSHA CEIL 300 ppm ACGIH TLV 20 ppm
Xylene	Xylol	1330-20-7	0.7	OSHA PEL 100 ppm ACGIH TLV 100 ppm ACGIH STEL 150 ppm
Nonhazardous as per 29 CFR 1910.1200.	None	None	24.5	None Established

SECTION 3: HAZARD IDENTIFICATION

Primary Route of Exposure:	Skin Absorption, Inhalation
Signs and Symptoms of Exposure:	Eye contact may cause severe eye irritation, redness, tearing and blurred vision. Prolonged or repeated skin contact may cause irritation, dermatitis and drying of the skin. Absorption through intact skin may contribute to an individual's overall exposure. Inhalation may cause respiratory system irritation and central nervous system depression (Narcosis) characterized by headache, dizziness, muscular weakness and fatigue. Inhalation of Toluene vapors above 200 ppm may result in impairment of coordination, increased reaction time and a bad taste in the mouth. May cause unconsciousness if exposure is excessive. Acetone LC ₅₀ : 16,000 ppm/4hr, rat; Acetone LD ₅₀ : 9.8 g/kg, rat; Toluene LC ₅₀ : 8,000 ppm/4hr, rat; Toluene LD ₅₀ : 5 g/kg, rat; Xylene LC ₅₀ : 5,000 ppm/4hr, rat; Xylene LD ₅₀ : 4.3 g/kg, rat.
Medical Conditions Aggravated by Exposure:	Exposure to this product may aggravate pre-existing skin and respiratory diseases. Individuals with neurological diseases should avoid exposure to hexane.

GenTite RRS

Material Safety Data Sheet

December 13, 2010

Page: 2

Chronic Effects:	May cause kidney and spleen damage. May cause brain cell and neuromuscular damage based upon animal studies.
Carcinogenicity:	Toluene is listed by IARC as a class 3, <i>unclassifiable as to carcinogenicity in humans</i> .

SECTION 4: FIRST AID MEASURES

First Aid Procedures:	If this material contacts the eyes, hold eyelids open and flush immediately with a gentle stream of water for at least 15 minutes, preferably at an eyewash fountain. Get medical attention. In case of skin contact, clean with rubbing alcohol first, followed immediately by washing affected area with soap and water. In case of inhalation, remove to fresh uncontaminated air. Administer oxygen if breathing is labored. Give artificial respiration if breathing has stopped. Get medical attention immediately if oxygen or artificial respiration are administered. In case of accidental ingestion, do not induce vomiting. Get medical attention and advise the physician of the nature of the material.
-----------------------	---

SECTION 5: FIRE FIGHTING PROCEDURES

Suitable Extinguishing Media:	Carbon dioxide, dry chemical, alcohol foam or water fog. Do not use a direct stream of water. Product will float and can be reignited on the surface of the water.
Hazardous Combustion Products:	Carbon dioxide and carbon monoxide, oxides of nitrogen, hydrogen chloride, various hydrocarbons, phenols, acrid smoke and irritating fumes.
Recommended Fire Fighting Procedures:	Wear impermeable protective clothing and self-contained breathing apparatus. Toxic fumes and vapors may be evolved.
Unusual Fire and Explosion Hazards:	Heat builds up pressure in closed containers. Cool with water stream.

SECTION 6: PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to Be Taken in Case Material is Released or Spilled:	Remove ignition sources. Absorb on inert material. Use non-sparking tools. Place in secure containers for disposal.
Precautions to Be Taken in Handling and Storing:	Keep away from heat, sparks, and open flames. Keep containers closed. Vapors of this material are heavier than air and will collect in low or confined areas. Containers, even those that have been emptied, can contain explosive vapors. Do not cut, drill, grind, weld or perform similar operations near containers. Static electricity may accumulate and create a fire hazard. Ground fixed equipment. Bond and ground all transfer containers and equipment.

SECTION 7: EXPOSURE CONTROLS / PERSONAL PROTECTION

Ventilation:	Use in a well-ventilated location.
Respiratory Protection:	If personal exposure concentrations cannot be maintained below the appropriate exposure limits using engineering controls, a NIOSH approved organic vapor air purifying respirator may be appropriate based on employer-determined exposure levels. Air supplied or SCBA respirators may be required when the measured chemical concentration exceeds the capacity of the air purifying respirator or when personal

GenTite RRS

Material Safety Data Sheet

December 13, 2010

Page: 3

Eye Protection:	exposure levels are unknown. Safety glasses with side shields may be needed as determined by end-user.
Skin Protection:	Chemical resistant gloves (e.g., neoprene or nitrile) may be required for direct handling. This is to be determined by the end-user.
Other:	Not required.
Work / Hygienic Practices:	Wash exposed skin prior to eating, drinking and smoking and at the end of each shift. Wash contaminated clothing prior to reuse.

SECTION 8: PHYSICAL AND CHEMICAL PROPERTIES

Appearance and Odor:	Yellow liquid with characteristic odor.		
Flash Point:	-18° C	Lower Explosive Limit:	1.2%
Method Used:	Unknown	Upper Explosive Limit:	13%
Evaporation Rate:	Unknown (Ether=1)	Boiling Point:	133° F
pH (undiluted product):	Unknown	Melting Point:	Unknown
Solubility in Water:	Not miscible or difficult to mix	Specific Gravity:	0.844 (Water=1)
Vapor Density:	2-4 (Air=1)	Percent Volatile:	75.7%
Vapor Pressure:	175 mm Hg @ 20° C		

SECTION 9: STABILITY AND REACTIVITY

Thermal Stability:	Stable
Hazardous Polymerization:	Will not occur
Conditions to Avoid:	Avoid flames, sparks or other sources of ignition. Incompatible with acids, alkalies and strong oxidizing agents.

SECTION 10: TRANSPORTATION

Regulatory Agency:	U.S.A., DOT, IMO
Proper Shipping Name:	Adhesives, <i>containing a flammable liquid</i>
Hazard Classification:	3
Identification Number:	UN1133
Packaging Group:	II
Labels Required:	Flammable
Other Requirements:	None

SECTION 11: MISCELLANEOUS INFORMATION

Additional Comments:	None
Date of Previous MSDS:	None
Changes Since Previous MSDS:	New product
Telephone Number for Additional Information:	(317) 575-7190

GenTite RRS

Material Safety Data Sheet

December 13, 2010

Page: 4

DISCLAIMER

The information contained herein is based on data considered accurate which has been obtained from other companies and organizations. However, no warranty or representation is expressed or implied that the information, is accurate, complete or representative. GenTite RRS, a division of GenFlex Roofing Systems, LLC, a subsidiary of Firestone Diversified Products, LLC, assumes no responsibility for injury to the buyer, the buyer's employees, or any third persons, if reasonable safety procedures are not followed. Additionally, GenTite RRS assumes no responsibility for injury to buyer, the buyer's employees, or any third persons caused by abnormal use of this material, even if reasonable safety procedures are followed.