# MOEN®

- DESCRIPTION
  Reflex™ pulldown system offers smooth operation, easy movement and secure docking
- Metal construction with spot resist stainless finish
- Duralock® quick connect installation
- PowerClean Spray
- Flexible supply lines with 3/8"CC fittings connect directly to supply stop
- High arc spout provides height and reach to fill or clean large pots while pull out wand provides the maneuverability for cleaning
- 360° rotating spout

#### **OPERATION**

- Lever style handle
- Temperature controlled by 100° arc of handle travel Operates with less than 5 lbs. of force
- Operates in stream or spray mode in the pulldown or retracted position

#### **FLOW**

- Flow is limited to 1.5 gpm (5.7 L/min) at 60 psi
- Power Boost™ Button activates boosted stream and boosted spray

### **CARTRIDGE**

1255™ Duralast™ cartridge for Single-Handle Faucets

#### **STANDARDS**

- Third party certified to IAPMO Green, ASME A112.18.1/CSA B125.1 and all applicable requirements referenced therein including
- Meets CalGreen and Georgia SB370 requirements
- Complies with California Proposition 65 and with the Federal Safe **Drinking Water Act**
- The backflow protection system in the device consists of two inde pendently operating check valves, a primary and a secondary which prevent backflow
- ADA **(** for lever handle

#### **WARRANTY**

Lifetime limited warranty against leaks, drips and finish defects to the original homeowner

10 year limited warranty when used in a multifamily installation 5 year limited warranty when used in a commercial installation

## **Specifications**



Single Handle **Pulldown Kitchen Faucet** 

**Model:** 87395SRS

**NOTE:** THIS FAUCET IS DESIGNED TO BE INSTALLED THROUGH 1, 2, 3 and 4 HOLE, 1-1/2" (38mm) MIN. DIA. (1 HOLE FOR SOAP DISPENSER)

