



84" TropoAir Titan

Weight = 96 lbs. in box

Weight = 85 lbs. out of box

MODEL #6HE84+LK



REQUIREMENTS

MECHANICAL:

Fan must be attached to a securely anchored electrical junction box that is rated for ceiling fans. Fan must also be mounted at least 10 feet above floor level.

ELECTRICAL:

Requires a grounded electrical supply line of 120 volts, 60Hz, 1 amp circuit.

FEATURES

MOTOR SPECS:

35W DC Motor

LOCATION USE:

This fan is rated cETLus and meets the standard for UL-507 and CAN/CSA-C22.2 No. 113.

WARRANTY:

Limited Lifetime Indoor & 10-Year Outdoor

OPTIONS

AVAILABLE FINISHES:

Pure White	Part #88252-88282
Brushed Nickel	Part #88251-88280
Oil Rubbed Bronze	Part #88250-88279

BLADES:

Match Fan Finish and also available in 72".

CONTROL:

Six speeds and reversing function is controlled by the included Hand Held remote control. An In-Wall Transmitter is also available.

LIGHTING:

An optional light fixture is **INCLUDED** with unit along with a cover if a light is not desired. Light kit consist of two medium base 60W max sockets. Included are two 13W CFL bulbs.

DOWNROD:

The fan comes with a nom. 3/4" diameter x 9" long down-rod. Optional down-rods are available in 12", 24", 36", 48", 60" and 72" lengths. A down-rod coupler is available for installations requiring a down-rod longer than 72". Fan can be mounted on a sloped ceiling up to 35°.

PERFORMANCE

AIRFLOW/ENERGY EFFICIENCY INFO

Fan Speed	RPM	CFM/ Watt	WATT	CFM
High	85/74	451	31.8/18.5	14352
Med	63/53	848	12.2/7.8	10347
Low	42/30	1517	4.9/3.4	5159

Dimensions:		
Canopy Diameter	Sweep Diameter	
5 15/16"	84"	
Downrod Length	Blade Depth	All Depth
9"	16"	19"
12"	19"	22"
24"	31"	34"
36"	43"	46"
48"	55"	58"
72"	79"	82"