## **Tresham**®



One-piece compact elongated toilet with skirted trapway, 1.28 gpf K-3981

#### Features

- One-piece toilets integrate the tank and bowl into a seamless, easy-to-clean design
- Compact elongated bowl offers added comfort while occupying the same space as a round-front bowl
- Comfort Height<sup>®</sup> feature offers chair-height seating that makes sitting down and standing up easier for most adults
- Skirted trapway simplifies cleaning
- Left-hand Polished Chrome trip lever
- Patented ReadyLock<sup>®</sup> installation system, a simple solution for skirted toilets, saves time, hassle, and eliminates the need to drill into the floor for standard 12" (305 mm) rough-in
- Coordinates with other products in the Tresham collection
- Easy-to-flush canister design requires less force to actuate than a 3" (76 mm) flapper, and has 90% less exposed seal material which resists conditions that cause wear, tear, shrinkage and swelling
- Eligible for consumer rebates in some municipalities
- Quiet-Close™ compact elongated lid and seat prevents slamming
- Quick-Release<sup>™</sup> functionality allows seat to be removed easily from toilet for convenient cleaning
- 1.28 gpf (4.8 lpf)


#### Installation

- Standard 12" (305 mm) rough-in
- 10" and 14" (254 mm and 356 mm) rough-in kits also available
- Supply line sold separately

#### **Recommended Products/Accessories**

K-4108 PureWash® E750 Elongated bidet toilet seat with remote control K-5381 14" Rough-in Full Skirt Trap and Attachment System K-5383 10" Rough-in Full Skirt Trap and Attachment System K-9375 Trip Lever 1023457 Wax Ring/Hardware Kit

1265114 Connector Hose







# Rent Server

#### Codes/Standards

ASME A112.19.2/CSA B45.1 DOE - Energy Policy Act 1992 EPA WaterSense® California Energy Commission (CEC) ADA ICC/ANSI A117.1 CSA B651 OBC IAPMO Certification

# KOHLER<sup>®</sup> Toilets and Seats Limited Warranty


See website for detailed warranty information.





### **Tresham**®

One-piece compact elongated toilet with skirted trapway, 1.28 gpf **K-3981** 



#### **Technical Information**

All product dimensions are nominal.

l oilet type:	Floor-mount
Waste Outlet:	Floor
Bowl shape:	Compact elongated
Flush type:	AquaPiston
Trap passageway:	2-1/8" (54 mm)
Water surface size:	9-5/8" x 6-7/8" (245 mm x 174 mm)
Rim to water surface:	5-3/8" (137 mm)
Rough-in:	12" (305 mm)
Seat-mounting holes:	5-1/2" (140 mm)

#### Notes

Install this product according to the installation instructions.

For back-to-back toilet installations: Use only a 45° double wye fitting.

ADA, OBC, CSA B651 compliant when installed to the specific requirements of these regulations.

Plumbing codes may require elongated toilets and elongated, open-front seats in public bathrooms.

Accessibility standards may require controls to be located on the open side of the toilet.

