

CEDAR TAN

CEDAR TAN

CEDAR TAN

CEDAR TAN



**CAUTION!** Contains ethylene glycol. Use in well-ventilated area. Do not get in eyes or on skin. Do not ingest. Use gloves and safety glasses. **In an emergency**, call your poison control center at 1(800) 222-1222. See Safety Data Sheet (SDS) for additional information. For an SDS, contact your supplier or visit [dap.com](http://dap.com). **KEEP OUT OF REACH OF CHILDREN.**

**¡PRECAUCIÓN!** Contiene etilenglicol. Use en un área bien ventilada. No permita el contacto con los ojos o la piel. No lo ingiere. Use guantes y gafas de seguridad. **En caso de emergencia**, llame a un centro de control de envenenamiento al 1-800-222-1222. Para más información, consulte la Hoja de datos de seguridad (SDS). Para obtener una SDS, comuníquese con su proveedor o visite [dap.com](http://dap.com). **MANTENGASE FUERA DEL ALCANCE DE LOS NIÑOS.**

**⚠ WARNING:** Cancer & Reproductive Harm – [www.P65warnings.ca.gov](http://www.P65warnings.ca.gov)

**ADVERTENCIA:** Cáncer y Daños al Sistema Reproductivo

**LIFETIME GUARANTEE:** DAP Products Inc. warrants this product for sealant purposes during the lifetime of your home when applied as directed within one year of purchase. If product fails to perform, call DAP Products Inc., Technical Customer Service at **1-888-DAP-TIPS** for replacement product or sales price refund. Have your sales receipt and cartridge available. DAP is not liable for incidental or consequential damages.

**Para obtener las instrucciones y garantía en español, llame al 1-888-DAP-TIPS o visite [dap.com](http://dap.com).**

**QUESTIONS/¿PREGUNTAS?**

Call/Llame al  
**1-888-DAP-TIPS** or  
visit/o visite [dap.com](http://dap.com)  
& click on/y pulse en  
"Ask the Expert."

**DAP Products Inc.**  
Baltimore, MD 21224

Made in the USA  
with U.S. and  
globally sourced  
materials.

[dap.com](http://dap.com)

# DYNAFLEX

# 230



**SUPERIOR FLEXIBILITY  
& CRACK PROOF**

- 100% Waterproof
- Seals Joints Up To 2" Wide
- 2 Hour Paint Ready
- Ideal for Wood, Composite & PVC Trim

**PREMIUM ELASTOMERIC  
INTERIOR / EXTERIOR SEALANT**

## Window, Door, Siding & Trim

Read back panel for cautions!  
¡Lea las precauciones en el  
panel posterior!

**10.1 fl oz (300 mL)**

**DAP® DYNAFLEX 230®** is a premium elastomeric window, door & siding sealant with silicone-like toughness. Combines outstanding durability, adhesion & flexibility with easy tooling, paintability, low odor & water clean-up. Highly flexible to handle joint movement without cracking. Cured sealant is mold & mildew resistant. DAP® DYNAFLEX 230® is a premium latex sealant with the performance characteristics of non-industrial acetoxy silicone products.

### ADHERES TO:

Wood, Composite Wood, PVC Trimboard, Vinyl, Aluminum, Metal, Fiber Cement, Concrete, Masonry, Brick, Stone, Stucco, Glass

### SPECIFICATIONS

ASTM C920, Type S, Grade NS, Class 25.  
Use NT, G, A, M. ASTM C834, Federal Spec TT-S-00230C, Type II, Class A

### PHYSICAL PROPERTIES

|                          |                                                                                     |
|--------------------------|-------------------------------------------------------------------------------------|
| <b>App. Temp Range:</b>  | 40°F to 100°F                                                                       |
| <b>Ideal Bead Size:</b>  | 3/8" (recommended)                                                                  |
| <b>Coverage:</b>         | 55 lin ft at 3/16" dia. bead                                                        |
| <b>Skin Time:</b>        | 15 minutes                                                                          |
| <b>Tack Free Time:</b>   | 30 minutes                                                                          |
| <b>Full Cure Time:</b>   | 7-14 days depending on joint depth, temperature, humidity & substrate               |
| <b>Paint Ready Time:</b> | 2-4 hours w/latex or oil-based paints. Use latex-based primer for oil-based paints. |
| <b>Water Ready Time:</b> | 24 hours                                                                            |
| <b>Joint Movement:</b>   | +/-25%, Stays flexible                                                              |
| <b>Mold Resistance:</b>  | Cured sealant is mold & mildew resistant                                            |
| <b>Odor:</b>             | Low                                                                                 |
| <b>Clean-Up:</b>         | Water                                                                               |
| <b>VOC Content:</b>      | NCCS Calif. ARB VOC <1.5 wt/wt% (VOC 39 g/L)                                        |
| <b>Shelf Life:</b>       | 12 months (unopened/cool & dry conditions)                                          |

**FOR BEST RESULTS:** Apply in temps. above 40°F. Do not apply when rain/freezing temps. are forecasted before full cure can occur. Do not use below waterline. Joint size should not exceed 2" wide x 1/2" deep. If joint depth exceeds 1/2", use foam backer rod. Store away from extreme heat/cold.

**INSTRUCTIONS:** 1. Surface must be clean, dry & free of caulk. 2. Cut nozzle at 45° angle to desired bead size. 3. Load into caulk gun. 4. Fill gap with sealant. 5. Smooth bead. 6. Clean up excess uncured sealant with damp sponge before it skins over. Cured sealant must be cut or scraped away. 7. Allow to dry 2-4 hours before painting with latex or oil-based paints. Cool or humid conditions or type of paint used may require longer dry time. 8. Reseal cartridge for storage & reuse.