



STORE+®

60" x 30" Vikrell® bath/shower with Aging in Place backerboards, left above-floor drain

71470118



Features

- Tongue-and-groove modular design allows for easy installation during any phase of construction
- Includes four rimmed shelves, two caddies, two hooks, and two soap dishes with towel bar
- Dishwasher-safe shelves and bins snap into place; no tools required
- Holds up to 30 bottles
- Easy-to-clean, durable high-gloss finish
- Factory-installed Aging in Place backerboards for future grab bar installation
- Innovative Dry-Block™ seal and channeled water containment system form watertight seams

Material

- Compression-molded from our exclusive solid Vikrell® material

Installation

- Alcove
- Caulk-free installation
- Above-floor-drain (AFD) rough-in
- Left drain

Recommended Products/Accessories

K-23726 Drain treatment
K-23733 Vikrell® cleaner

Included Components

71171112 60" x 30" Vikrell® bath, left above-floor drain
71474106 60" x 30" Vikrell® bath/shower wall set with Aging in Place backerboards



Codes/Standards

CSA B45.5/IAPMO Z124
ASTM E162
ASTM E662


STERLING® Vikrell® or Acrylic Baths and Shower Bases Ten-Year Limited Warranty


See website for detailed warranty information.

Available Colors/Finishes

Color tiles intended for reference only.

Color Code Description

| | | |
|---|---|-------|
|  | 0 | White |
|---|---|-------|



Technical Information

All product dimensions are nominal.

| | |
|------------------------|------------------------------|
| Drain location: | Left |
| Basin area, bottom: | 45" x 20" (1143 mm x 508 mm) |
| Basin area, top: | 53" x 23" (1346 mm x 584 mm) |
| Weight: | 126.5 lbs (57.4 kg) |
| Water depth: | 11-1/4" (286 mm) |
| Water capacity: | 44 gal (166.6 L) |
| Minimum flat for door: | 2-3/4" (70 mm) |
| Maximum door height: | 59" (1499 mm) |
| Maximum door width: | 57-11/16" (1465 mm) |

Notes

Install this product according to the installation instructions.

Studs should be positioned roughly as shown. Double studding is recommended for pivot shower door installations.

Attach grab bars at the specified backer board locations only.

Felt pad not required for installation.