

SECTION 1: IDENTIFICATION

Product Identifier

Product Form: Mixture

Product Name: Types M, N, Stucco & Roof Tile Cement

Synonyms: Masonry cements, Type N, Type S and Stucco

Chemical Family: Calcium Compounds

Intended Use of the Product

Use of the Substance/Mixture: Building materials, construction.

Name, Address, and Telephone of the Responsible Party

Company

Roanoke Cement Company LLC

6071 Catawba Road

Troutville, VA 24175

Pennsuco Cement Company LLC

1100 NW 121st Way

Medley, FL 33178

Emergency Telephone Number CHEMTREC – 800-424-9300

SECTION 2: HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

Classification (GHS-US)

Skin Irrit. 2 H315

Eye Dam. 1 H318

Skin Sens. 1 H317

Carc. 1A H350

STOT SE 3 H335

STOT RE 1 H372

Full text of H-phrases: see section 16

Label Elements

GHS-US Labeling

Hazard Pictograms (GHS-US)

:



GHS05



GHS07



GHS08

Signal Word (GHS-US)

: Danger

Hazard Statements (GHS-US)

: H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction.

H318 - Causes serious eye damage.

H335 - May cause respiratory irritation.

H350 - May cause cancer.

H372 - Causes damage to organs through prolonged or repeated exposure.

Precautionary Statements (GHS-US)

: P261 - Avoid breathing dust.

P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.

P280 - Wear protective gloves, protective clothing, and eye protection.

P302+P352 - IF ON SKIN: Wash with plenty of water.

P304+P340 - IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Types M, N, Stucco & Roof Tile Cement

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

P308+P313 - If exposed or concerned: Get medical advice/attention.
P312 - Call a poison center or doctor if you feel unwell.
P314 - Get medical advice/attention if you feel unwell.
P321 - Specific treatment (see section 4 on this SDS).
P332+P313 - If skin irritation occurs: Get medical advice/attention.
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
P362 - Take off contaminated clothing and wash it before reuse.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P501 - Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations.

Other Hazards

Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions. Repeated or prolonged exposure to respirable (airborne) crystalline silica dust will cause lung damage in the form of silicosis. Symptoms will include progressively more difficult breathing, cough, fever, and weight loss. Product becomes alkaline when exposed to moisture or water. Exposure can cause chemical burns, or severe irritation of the mucous membranes, skin, eyes, and other exposed areas.

Unknown Acute Toxicity (GHS-US) Not available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

Name	Product Identifier	% (w/w)
Cement, portland, chemicals	(CAS No) 65997-15-1	100
Contains (Name)	Product Identifier	% (w/w)
Limestone	(CAS No) 1317-65-3	30 - 35
Gypsum (Ca(SO ₄).2H ₂ O)	(CAS No) 13397-24-5	3 - 6
Quartz	(CAS No) 14808-60-7	0 - 5
Iron oxide (Fe ₂ O ₃)	(CAS No) 1309-37-1	1 - 4
Chromium, ion (Cr 6+)	(CAS No) 18540-29-9	< 0.05

Full text of H-phrases: see section 16

*The specific chemical identity and/or exact percentage of composition have been withheld as a trade secret within the meaning of the OSHA Hazard Communication Standard [29 CFR 1910.1200].

**A range of concentration as prescribed by Controlled Products Regulations has been used where necessary, due to varying composition.

***More than one of the ranges of concentration prescribed by Controlled Products Regulations has been used where necessary, due to varying composition.

****Hexavalent chromium is included due to dermal sensitivity associated with the component.

SECTION 4: FIRST AID MEASURES

Description of First Aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label if possible).

Inhalation: Inhalation of large amounts of Types M, N, Stucco & Roof Tile Cement requires immediate medical attention. Remove to fresh air and keep at rest in a position comfortable for breathing. Obtain medical attention if breathing difficulty persists.

Skin Contact: Heavy exposure Types M, N, Stucco & Roof Tile Cement dust, wet mortar or associated water requires prompt attention. Remove contaminated clothing. Gently wash with plenty of soap and water followed by rinsing with water for at least 15 minutes. Seek medical attention immediately. Wash contaminated clothing before reuse.

Eye Contact: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing for at least 60 minutes. Seek medical attention immediately.

Ingestion: Do not induce vomiting. Rinse mouth. Seek medical attention if any problems arise.

Most Important Symptoms and Effects Both Acute and Delayed

General: Causes serious eye damage. May cause an allergic skin reaction. May cause cancer. Causes skin irritation. May cause respiratory irritation. May cause damage to organs through prolonged or repeated exposure.

Types M, N, Stucco & Roof Tile Cement

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Inhalation: Repeated exposure to respirable (airborne) crystalline silica dust will cause lung damage in the form of silicosis. May cause respiratory irritation.

Skin Contact: May cause an allergic skin reaction. Causes skin irritation. Symptoms may include: Redness, pain, swelling, itching, burning, dryness, and dermatitis.

Eye Contact: Causes serious eye damage. Symptoms may include: Redness. Pain. Blurred vision. Severe burns.

Ingestion: Ingestion is likely to be harmful or have adverse effects.

Chronic Symptoms: May cause cancer. May cause damage to organs through prolonged or repeated exposure. Repeated or prolonged exposure to respirable (airborne) crystalline silica dust will cause lung damage in the form of silicosis. Symptoms will include progressively more difficult breathing, cough, fever, and weight loss.

Indication of Any Immediate Medical Attention and Special Treatment Needed

If you feel unwell, seek medical advice (show the label where possible).

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media: No fire hazard present for this material.

Unsuitable Extinguishing Media: No fire hazard present for this material.

Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not flammable.

Explosion Hazard: Product is not explosive.

Reactivity: Reacts slowly with water forming hydrated compounds, releasing heat and producing a strong alkaline solution until reaction is substantially complete.

Advice for Firefighters

Precautionary Measures Fire: No fire hazard present for this material.

Firefighting Instructions: No fire hazard present for this material.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Carbon dioxide, carbon monoxide, sulfur oxides and metal oxide/oxides

Other Information: Refer to Section 9 for flammability properties.

Reference to Other Sections

Refer to section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Do not breathe dust.

For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Stop spill if safe to do so. Eliminate ignition sources. Ventilate area.

Environmental Precautions Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has entered the environment, including waterways, soil or air. Materials can enter waterways through drainage systems.

Methods and Material for Containment and Cleaning Up

For Containment: Contain and collect as any solid.

Reference to Other Sections

See Heading 8. Exposure controls and personal protection. For further information refer to section 13.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Additional Hazards When Processed: Do not breathe dust.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

Types M, N, Stucco & Roof Tile Cement

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations. Good housekeeping is needed during storage, transfer, handling, and use of this material to avoid excessive dust accumulation.

Storage Conditions: Store in a dry, and well-ventilated place. Keep container closed when not in use. Keep/Store away from incompatible materials. Store away from oxidizers, combustible materials, and all ignition sources.

Incompatible Materials: Strong acids. Strong bases. Strong oxidizers. Wet cement is alkaline and is incompatible with acids, ammonium salts and aluminum metal. Cement dissolves in hydrofluoric acid, producing corrosive silicon tetrafluoride gas. Cement reacts with water to form silicates and calcium hydroxide. Silicates react with powerful oxidizers such as fluorine, boron trifluoride, chlorine trifluoride, manganese trifluoride, and oxygen difluoride.

Specific End Use(s)

Building materials, construction.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

For substances listed in section 3 that are not listed here, there are no established Exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), NIOSH (REL), OSHA (PEL), Canadian provincial governments, or the Mexican government

Cement, portland, chemicals (65997-15-1)		
Mexico	OEL TWA (mg/m ³)	10 mg/m ³
Mexico	OEL STEL (mg/m ³)	20 mg/m ³
USA ACGIH	ACGIH TWA (mg/m ³)	1 mg/m ³ (particulate matter containing no asbestos and <1% crystalline silica, respirable fraction)
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction)
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	10 mg/m ³ (total dust) 5 mg/m ³ (respirable dust)
USA IDLH	US IDLH (mg/m ³)	5000 mg/m ³
Alberta	OEL TWA (mg/m ³)	10 mg/m ³
British Columbia	OEL TWA (mg/m ³)	10 mg/m ³ (total particulate matter containing no Asbestos and <1% Crystalline silica-total particulate) 3 mg/m ³ (particulate matter containing no Asbestos and <1% Crystalline silica-respirable particulate)
Manitoba	OEL TWA (mg/m ³)	1 mg/m ³ (particulate matter containing no Asbestos and <1% Crystalline silica-respirable fraction)
New Brunswick	OEL TWA (mg/m ³)	10 mg/m ³ (particulate matter containing no Asbestos and <1% Crystalline silica)
Newfoundland & Labrador	OEL TWA (mg/m ³)	1 mg/m ³ (particulate matter containing no Asbestos and <1% Crystalline silica-respirable fraction)
Nova Scotia	OEL TWA (mg/m ³)	1 mg/m ³ (particulate matter containing no Asbestos and <1% Crystalline silica-respirable fraction)
Nunavut	OEL TWA (mg/m ³)	5 mg/m ³ (respirable mass) 10 mg/m ³ (total mass)
Northwest Territories	OEL TWA (mg/m ³)	5 mg/m ³ (respirable mass) 10 mg/m ³ (total mass)
Ontario	OEL TWA (mg/m ³)	1 mg/m ³ (containing no Asbestos and <1% Crystalline silica-respirable)
Prince Edward Island	OEL TWA (mg/m ³)	1 mg/m ³ (particulate matter containing no Asbestos and <1% Crystalline silica-respirable fraction)
Québec	VEMP (mg/m ³)	10 mg/m ³ (containing no Asbestos and <1% Crystalline silica-total dust) 5 mg/m ³ (containing no Asbestos and <1% Crystalline silica-respirable dust)

Types M, N, Stucco & Roof Tile Cement

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Saskatchewan	OEL STEL (mg/m ³)	20 mg/m ³
Saskatchewan	OEL TWA (mg/m ³)	10 mg/m ³
Yukon	OEL STEL (mg/m ³)	20 mg/m ³
Yukon	OEL TWA (mg/m ³)	30 mppcf 10 mg/m ³
Limestone (1317-65-3)		
Mexico	OEL TWA (mg/m ³)	10 mg/m ³
Mexico	OEL STEL (mg/m ³)	20 mg/m ³
USA OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction)
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	10 mg/m ³ (total dust) 5 mg/m ³ (respirable dust)
Alberta	OEL TWA (mg/m ³)	10 mg/m ³
British Columbia	OEL STEL (mg/m ³)	20 mg/m ³ (total dust)
British Columbia	OEL TWA (mg/m ³)	10 mg/m ³ (total dust) 3 mg/m ³ (respirable fraction)
New Brunswick	OEL TWA (mg/m ³)	10 mg/m ³ (particulate matter containing no Asbestos and <1% Crystalline silica)
Nunavut	OEL TWA (mg/m ³)	5 mg/m ³ (respirable mass) 10 mg/m ³ (total mass)
Northwest Territories	OEL TWA (mg/m ³)	5 mg/m ³ (respirable mass) 10 mg/m ³ (total mass)
Québec	VEMP (mg/m ³)	10 mg/m ³ (Limestone, containing no Asbestos and <1% Crystalline silica-total dust)
Saskatchewan	OEL STEL (mg/m ³)	20 mg/m ³
Saskatchewan	OEL TWA (mg/m ³)	10 mg/m ³
Yukon	OEL STEL (mg/m ³)	20 mg/m ³
Yukon	OEL TWA (mg/m ³)	30 mppcf 10 mg/m ³
Gypsum (Ca(SO₄).2H₂O) (13397-24-5)		
Mexico	OEL TWA (mg/m ³)	10 mg/m ³ (inhalable fraction)
USA ACGIH	ACGIH TWA (mg/m ³)	10 mg/m ³ (inhalable fraction)
USA OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction)
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	10 mg/m ³ (total dust) 5 mg/m ³ (respirable dust)
Alberta	OEL TWA (mg/m ³)	10 mg/m ³
British Columbia	OEL STEL (mg/m ³)	20 mg/m ³ (total dust)
British Columbia	OEL TWA (mg/m ³)	10 mg/m ³ (total dust) 3 mg/m ³ (respirable fraction)
Manitoba	OEL TWA (mg/m ³)	10 mg/m ³ (inhalable fraction)
Newfoundland & Labrador	OEL TWA (mg/m ³)	10 mg/m ³ (inhalable fraction)
Nova Scotia	OEL TWA (mg/m ³)	10 mg/m ³ (inhalable fraction)
Nunavut	OEL TWA (mg/m ³)	5 mg/m ³ (respirable mass) 10 mg/m ³ (total mass)
Northwest Territories	OEL TWA (mg/m ³)	5 mg/m ³ (respirable mass) 10 mg/m ³ (total mass)
Ontario	OEL TWA (mg/m ³)	10 mg/m ³ (inhalable)
Prince Edward Island	OEL TWA (mg/m ³)	10 mg/m ³ (inhalable fraction)
Québec	VEMP (mg/m ³)	10 mg/m ³ (containing no Asbestos and <1% Crystalline silica-total dust) 5 mg/m ³ (containing no Asbestos and <1% Crystalline

Types M, N, Stucco & Roof Tile Cement

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

		silica-respirable dust)
Saskatchewan	OEL STEL (mg/m ³)	20 mg/m ³
Saskatchewan	OEL TWA (mg/m ³)	10 mg/m ³
Yukon	OEL STEL (mg/m ³)	20 mg/m ³
Yukon	OEL TWA (mg/m ³)	30 mppcf 10 mg/m ³
Quartz (14808-60-7)		
Mexico	OEL TWA (mg/m ³)	0.1 mg/m ³ (respirable fraction)
USA ACGIH	ACGIH TWA (mg/m ³)	0.025 mg/m ³ (respirable fraction)
USA ACGIH	ACGIH chemical category	A2 - Suspected Human Carcinogen
USA OSHA	OSHA PEL (STEL) (mg/m ³)	250 mppcf/%SiO ₂ +5, 10mg/m ³ /%SiO ₂ +2
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	0.05 mg/m ³ (respirable dust)
USA IDLH	US IDLH (mg/m ³)	50 mg/m ³ (respirable dust)
Alberta	OEL TWA (mg/m ³)	0.025 mg/m ³ (respirable particulate)
British Columbia	OEL TWA (mg/m ³)	0.025 mg/m ³ (respirable)
Manitoba	OEL TWA (mg/m ³)	0.025 mg/m ³ (respirable fraction)
New Brunswick	OEL TWA (mg/m ³)	0.1 mg/m ³ (respirable fraction)
Newfoundland & Labrador	OEL TWA (mg/m ³)	0.025 mg/m ³ (respirable fraction)
Nova Scotia	OEL TWA (mg/m ³)	0.025 mg/m ³ (respirable fraction)
Nunavut	OEL TWA (mg/m ³)	0.1 mg/m ³ (respirable mass) 0.3 mg/m ³ (total mass)
Northwest Territories	OEL TWA (mg/m ³)	0.1 mg/m ³ (respirable mass) 0.3 mg/m ³ (total mass)
Ontario	OEL TWA (mg/m ³)	0.10 mg/m ³ (designated substances regulation-respirable)
Prince Edward Island	OEL TWA (mg/m ³)	0.025 mg/m ³ (respirable fraction)
Québec	VEMP (mg/m ³)	0.1 mg/m ³ (respirable dust)
Saskatchewan	OEL TWA (mg/m ³)	0.05 mg/m ³ (respirable fraction)
Yukon	OEL TWA (mg/m ³)	300 particle/mL
Iron oxide (Fe₂O₃) (1309-37-1)		
Mexico	OEL TWA (mg/m ³)	5 mg/m ³
Mexico	OEL STEL (mg/m ³)	10 mg/m ³
USA ACGIH	ACGIH TWA (mg/m ³)	5 mg/m ³ (respirable fraction)
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA OSHA	OSHA PEL (TWA) (mg/m ³)	10 mg/m ³ (fume) 15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction)
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	5 mg/m ³ (dust and fume)
USA IDLH	US IDLH (mg/m ³)	2500 mg/m ³ (dust and fume)
Alberta	OEL TWA (mg/m ³)	5 mg/m ³ (respirable)
British Columbia	OEL STEL (mg/m ³)	10 mg/m ³ (fume)
British Columbia	OEL TWA (mg/m ³)	10 mg/m ³ (total particulate matter containing no Asbestos and <1% Crystalline silica-total particulate) 3 mg/m ³ (particulate matter containing no Asbestos and <1% Crystalline silica-respirable particulate) 5 mg/m ³ (dust and fume)
Manitoba	OEL TWA (mg/m ³)	5 mg/m ³ (respirable fraction)
New Brunswick	OEL TWA (mg/m ³)	5 mg/m ³ (particulate matter containing no Asbestos and <1% Crystalline silica, dust and fume) 10 mg/m ³ (regulated under Rouge-particulate matter containing no Asbestos and <1% Crystalline silica)
Newfoundland & Labrador	OEL TWA (mg/m ³)	5 mg/m ³ (respirable fraction)
Nova Scotia	OEL TWA (mg/m ³)	5 mg/m ³ (respirable fraction)

Types M, N, Stucco & Roof Tile Cement

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Nunavut	OEL TWA (mg/m ³)	5 mg/m ³ (respirable mass) 10 mg/m ³ (total mass)
Northwest Territories	OEL TWA (mg/m ³)	5 mg/m ³ (respirable mass) 10 mg/m ³ (total mass)
Ontario	OEL TWA (mg/m ³)	5 mg/m ³ (respirable)
Prince Edward Island	OEL TWA (mg/m ³)	5 mg/m ³ (respirable fraction)
Québec	VEMP (mg/m ³)	5 mg/m ³ (dust and fume) 10 mg/m ³ (containing no Asbestos and <1% Crystalline silica, regulated under Rouge-total dust)
Saskatchewan	OEL STEL (mg/m ³)	10 mg/m ³ (dust and fume) 20 mg/m ³ (regulated under Rouge)
Saskatchewan	OEL TWA (mg/m ³)	5 mg/m ³ (dust and fume) 10 mg/m ³ (regulated under Rouge)
Yukon	OEL STEL (mg/m ³)	10 mg/m ³ (fume) 20 mg/m ³ (regulated under Rouge)
Yukon	OEL TWA (mg/m ³)	5 mg/m ³ (fume) 30 mppcf (regulated under Rouge) 10 mg/m ³ (regulated under Rouge)
Chromium, ion (Cr 6+) (18540-29-9)		
USA OSHA	OSHA PEL (TWA) (mg/m ³)	5 µg/m ³

Exposure Controls

Appropriate Engineering Controls: Ensure adequate ventilation, especially in confined areas. Clean water should always be readily available for skin and (emergency) eye washing. Ensure all national/local regulations are observed.

Personal Protective Equipment: Protective goggles or safety glasses with side shields. Gloves. Protective clothing. Dust formation: dust mask.



Materials for Protective Clothing: Wear suitable materials and fabrics.

Hand Protection: Wear protective gloves.

Eye Protection: Goggles or safety glasses with side shields.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: Use NIOSH-approved dust mask if dust has the potential to become airborne.

Environmental Exposure Controls: Do not allow the product to be released into the environment.

Consumer Exposure Controls: Do not eat, drink or smoke during use.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

Physical State	: Solid
Appearance	: Not available
Odor	: Odorless
Odor Threshold	: Not available
pH	: >11.5 (in water)
Evaporation Rate	: Not available
Melting Point	: Not available
Freezing Point	: Not available
Boiling Point	: Not available
Flash Point	: Not available
Auto-ignition Temperature	: Not available
Decomposition Temperature	: Not available
Flammability (solid, gas)	: Not available

Types M, N, Stucco & Roof Tile Cement

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Lower Flammable Limit	: Not available
Upper Flammable Limit	: Not available
Vapor Pressure	: Not available
Relative Vapor Density at 20 °C	: Not available
Relative Density	: Not available
Specific Gravity	: Not available
Solubility	: Water: 0.1 - 1 % Slightly soluble
Partition Coefficient: N-Octanol/Water	: Not available
Viscosity	: Not available
Explosion Data – Sensitivity to Mechanical Impact	: Not expected to present an explosion hazard due to mechanical impact.
Explosion Data – Sensitivity to Static Discharge	: Not expected to present an explosion hazard due to static discharge.

SECTION 10: STABILITY AND REACTIVITY

Reactivity: Reacts slowly with water forming hydrated compounds, releasing heat and producing a strong alkaline solution until reaction is substantially complete.

Chemical Stability: Stable under recommended handling and storage conditions (see section 7).

Possibility of Hazardous Reactions: Hazardous polymerization will not occur.

Conditions to Avoid: Incompatible materials.

Incompatible Materials: Strong acids, strong bases, strong oxidizers. Contact of dust with strong oxidizers may cause fire or explosion. Wet cement and cement clinker is alkaline and is incompatible with acids, ammonium salts and aluminum metal. Cement dissolves in hydrofluoric acid, producing corrosive silicon tetrafluoride gas. Cement reacts with water to form silicates and calcium hydroxide. Silicates react with powerful oxidizers such as fluorine, boron trifluoride, chlorine trifluoride, manganese trifluoride, and oxygen difluoride.

Hazardous Decomposition Products: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects - Product

Acute Toxicity: Not classified

LD50 and LC50 Data: Not available

Skin Corrosion/Irritation: Causes skin irritation.

pH: 12 (in water) (ASTM D 1293-95)

Serious Eye Damage/Irritation: Causes serious eye damage.

pH: 12 (in water) (ASTM D 1293-95)

Respiratory or Skin Sensitization: May cause an allergic skin reaction.

Germ Cell Mutagenicity: Not classified

Teratogenicity: Not classified

Carcinogenicity: May cause cancer

Specific Target Organ Toxicity (Repeated Exposure): Causes damage to organs through prolonged or repeated exposure.

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): May cause respiratory irritation.

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: Repeated exposure to respirable (airborne) crystalline silica dust will cause lung damage in the form of silicosis. May cause respiratory irritation.

Symptoms/Injuries After Skin Contact: May cause an allergic skin reaction. Causes skin irritation. Symptoms may include: Redness, pain, swelling, itching, burning, dryness, and dermatitis.

Symptoms/Injuries After Eye Contact: Causes serious eye damage. Symptoms may include: Redness. Pain. Blurred vision. Severe burns.

Symptoms/Injuries After Ingestion: Ingestion is likely to be harmful or have adverse effects.

Chronic Symptoms: May cause cancer. May cause damage to organs through prolonged or repeated exposure. Repeated or prolonged exposure to respirable (airborne) crystalline silica dust will cause lung damage in the form of silicosis. Symptoms will include progressively more difficult breathing, cough, fever, and weight loss.

Types M, N, Stucco & Roof Tile Cement

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

Quartz (14808-60-7)	
LD50 Oral Rat	> 5000 mg/kg
LD50 Dermal Rat	> 5000 mg/kg
Iron oxide (Fe2O3) (1309-37-1)	
LD50 Oral Rat	> 10000 mg/kg
Quartz (14808-60-7)	
IARC Group	1
National Toxicology Program (NTP) Status	Known Human Carcinogens.
OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen list.
Iron oxide (Fe2O3) (1309-37-1)	
IARC Group	3
Chromium, ion (Cr 6+) (18540-29-9)	
IARC Group	1
OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen list.
OSHA Specifically Regulated Carcinogen List	In OSHA Specifically Regulated Carcinogen list.

SECTION 12: ECOLOGICAL INFORMATION

Toxicity No additional information available

Chromium, ion (Cr 6+) (18540-29-9)	
LC50 Fish 1	36.2 mg/l (Exposure time: 96 h - Species: Pimephales promelas)
LC 50 Fish 2	7.6 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)

Persistence and Degradability Not available

Bioaccumulative Potential Not available

Mobility in Soil Not available

Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

Ecology – Waste Materials: Avoid release to the environment.

SECTION 14: TRANSPORT INFORMATION

In Accordance with DOT Not regulated for transport

In Accordance with IMDG Not regulated for transport

In Accordance with IATA Not regulated for transport

In Accordance with TDG Not regulated for transport

SECTION 15: REGULATORY INFORMATION

US Federal Regulations

Types M, N, Stucco & Roof Tile	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Delayed (chronic) health hazard
Cement, portland, chemicals (65997-15-1)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard
Limestone (1317-65-3)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	

Types M, N, Stucco & Roof Tile Cement

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Quartz (14808-60-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Delayed (chronic) health hazard
Iron oxide (Fe₂O₃) (1309-37-1)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	

US State Regulations

Quartz (14808-60-7)	
U.S. - California - Proposition 65 - Carcinogens List	WARNING: This product contains chemicals known to the State of California to cause cancer.

Cement, portland, chemicals (65997-15-1)	
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List	

Limestone (1317-65-3)	
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List	

Gypsum (Ca(SO₄).2H₂O) (13397-24-5)	
U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List	

Quartz (14808-60-7)	
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List	

Iron oxide (Fe₂O₃) (1309-37-1)	
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List	

Chromium, ion (Cr 6+) (18540-29-9)	
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List U.S. - Pennsylvania - RTK (Right to Know) List	

Canadian Regulations

Types M, N, Stucco & Roof Tile	
WHMIS Classification	Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects



Cement, portland, chemicals (65997-15-1)	
Listed on the Canadian DSL (Domestic Substances List) Listed on the Canadian IDL (Ingredient Disclosure List)	
WHMIS Classification	Class E - Corrosive Material Class D Division 2 Subdivision B - Toxic material causing other toxic effects

Limestone (1317-65-3)	
Listed on the Canadian NDSL (Non-Domestic Substances List)	
WHMIS Classification	Uncontrolled product according to WHMIS classification criteria

Types M, N, Stucco & Roof Tile Cement

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Quartz (14808-60-7)	
Listed on the Canadian DSL (Domestic Substances List)	
Listed on the Canadian IDL (Ingredient Disclosure List)	
IDL Concentration 1 %	
WHMIS Classification	Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects
Iron oxide (Fe₂O₃) (1309-37-1)	
Listed on the Canadian DSL (Domestic Substances List)	
Listed on the Canadian IDL (Ingredient Disclosure List)	
IDL Concentration 1 %	
WHMIS Classification	Uncontrolled product according to WHMIS classification criteria
Chromium, ion (Cr 6+) (18540-29-9)	
WHMIS Classification	Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Revision Date : 05/27/2015
Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

GHS Full Text Phrases:

Carc. 1A	Carcinogenicity Category 1A
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Skin Irrit. 2	Skin corrosion/irritation Category 2
Skin Sens. 1	Skin sensitization Category 1
STOT RE 1	Specific target organ toxicity (repeated exposure) Category 1
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H335	May cause respiratory irritation
H350	May cause cancer
H372	Causes damage to organs through prolonged or repeated exposure

"The information provided herein is believed by seller to be accurate at the time of preparation, or prepared from sources believed to be reliable. Health and safety precautions in this data sheet may not be adequate for all individuals or situations. Users have the responsibility to comply with all laws and procedures applicable to the safe handling and use of the product, to determine the suitability of the product for its intended use, and to understand possible hazards associated with mixing this product with other materials. SELLER MAKES NO WARRANTY, EXPRESS OR IMPLIED, CONCERNING THE PRODUCT, THE MERCHANTABILITY, OR FITNESS THEREOF FOR ANY PURPOSE, OR CONCERNING THE ACCURACY OF ANY INFORMATION PROVIDED BY SELLER".