






Dutdoot / Indoot Air ConditionerCooling / Heating

Equator 10,000 BTU Outdoor-Indoor 3-in-1 AIR CONDITIONER+HEATER+FAN 110V+Drip Pan+Pump

Control Panel





USES		
Unit Location	Cooling	Hot Air Exhaust
Outdoors Eg: Garden	Outdoors	Outdoors
Indoors Eg: Shop	Indoors	Outdoors
Outdoors Eg: Cabin	Indoors	Outdoors

FEATURES

Includes

- Remote Control
- Protective Cover
- 15ft. Hot Air Exhaust Kit
- 10¼" 2 Cold Air Hoses with Caps

Function

- Dual Outlet
- Timer Function
- Adjustable Speed
- AC + Heater + Fan
- Washable Air Filter
- Power-off Protection
- Compressor over-load shut off Protection

Material

- All Metal Construction
- IP 24 Rated Waterproof
- Anti-Rust and Anti-Corrosion Coating

Portability

- Freestanding
- No Installation Required
- Handle for easy Movement
- Universal 360° Casters with Brakes





DPK 2019

Model Color Color Capacity (Cooling/Heating) Air Volume Electrical Rated Power (Cooling/Heating) Rated Current (Cooling/Heating) Noise Level Indoor Temperature (Cooling/Heating) Operating Outdoor Temperature Refrigerant Water Drainage Water Tank Capacity Compressor Type Power Cord Length Cooling Hose Diameter Weight (Net/Gross) lbs Product Dimensions without Hose (HxWxD) inch Type of Shipping On With August 10,000 Btu / 6,200 Btu Turquoise Blue & Silver 10,000 Btu / 6,200 Btu 110v / 60Hz 110v / 60Hz 110v / 60Hz 110v / 50BB 100v / 1500W 9.1 A / 13.6 A 100v / 1500W 9.1 A	SPECIFICATIONS		
Capacity (Cooling/Heating) Air Volume Electrical Rated Power (Cooling/Heating) Rated Current (Cooling/Heating) Rated Current (Cooling/Heating) Roise Level Indoor Temperature (Cooling/Heating) Operating Outdoor Temperature Refrigerant Water Drainage Water Drainage Drain Hose / Water Tank Water Tank Capacity Compressor Type Power Cord Length Cooling Hose Diameter Weight (Net/Gross) Ibs Product Dimensions without Hose (HxWxD) inch Type of Shipping 10,000 Btu / 6,200 Btu 280 m³/h 110V / 60Hz 110V / 60	Model	OAC 4000	
Air Volume Electrical Rated Power (Cooling/Heating) Rated Current (Cooling/Heating) Rated Current (Cooling/Heating) Noise Level Indoor Temperature (Cooling/Heating) Operating Outdoor Temperature Refrigerant Refrigerant Water Drainage Water Tank Capacity Compressor Type Power Cord Length Cooling Hose Diameter Weight (Net/Gross) lbs Product Dimensions without Hose (HxWxD) inch Type of Shipping Power Cooling/Heating) 9.1 A / 13.00 1000W / 1500W 1000W / 1000W 1000W / 1500W 1000W / 100W 1000W / 1500W 1000W / 100W 10	Color	Turquoise Blue & Silver	
Electrical Rated Power (Cooling/Heating) Rated Current (Cooling/Heating) Rated Current (Cooling/Heating) Noise Level Indoor Temperature (Cooling/Heating) Operating Outdoor Temperature Refrigerant Refrigerant Refrigerant Rated Current (Cooling/Heating) So°F - 99°F Operating Outdoor Temperature Refrigerant Rated	Capacity (Cooling/Heating)	10,000 Btu / 6,200 Btu	
Rated Power (Cooling/Heating) Rated Current (Cooling/Heating) Noise Level Indoor Temperature (Cooling/Heating) Operating Outdoor Temperature Refrigerant Refrigerant Water Drainage Water Tank Capacity Compressor Type Power Cord Length Cooling Hose Diameter Weight (Net/Gross) Ibs Product Dimensions without Hose (HxWxD) inch Package Dimensions (HxWxD) inch Type of Shipping 1000W / 1500W 9.1 A / 13.6 A 55 dB 50°F - 99°F Pour Capacity Rater R 32 Drain Hose / Water Tank 0.8gal (3L) Rotary Postary Potary Poyer Cord Length 4½ inch 62 / 70½ Product Dimensions without Hose (HxWxD) inch 35 x 215% x 13% FedEx / UPS	Air Volume	280 m³/h	
Rated Current (Cooling/Heating) Noise Level Indoor Temperature (Cooling/Heating) Operating Outdoor Temperature Refrigerant Water Drainage Water Tank Capacity Compressor Type Power Cord Length Cooling Hose Diameter Weight (Net/Gross) lbs Product Dimensions without Hose (HxWxD) inch Package Dimensions (HxWxD) inch Type of Shipping P 50 B Drain Hose / Water Tank 0.8gal (3L) Construct Rotary Postary Potatry Rotary 8½ feet 4½ inch 22½ x 18½ x 11 35 x 21¼ x 11 FedEx / UPS	Electrical	110V / 60Hz	
Noise Level Indoor Temperature (Cooling/Heating) Operating Outdoor Temperature Refrigerant Refrigerant Ray Water Drainage Drain Hose / Water Tank Water Tank Capacity Compressor Type Rotary Power Cord Length Cooling Hose Diameter Weight (Net/Gross) Ibs Product Dimensions without Hose (HxWxD) inch Package Dimensions (HxWxD) inch Type of Shipping 55 dB 50°F - 99°F 23°F - 131°F R 32 Drain Hose / Water Tank 0.8gal (3L) Rotary 98½ feet 4½ inch 4½ inch 22½ x 18½ x 11 35 x 215¼ x 13¾ FedEx / UPS	Rated Power (Cooling/Heating)	1000W / 1500W	
Indoor Temperature (Cooling/Heating) Operating Outdoor Temperature Refrigerant Refrigerant Water Drainage Water Tank Capacity Compressor Type Power Cord Length Cooling Hose Diameter Weight (Net/Gross) lbs Product Dimensions without Hose (HxWxD) inch Package Dimensions (HxWxD) inch Type of Shipping Type 123°F - 131°F R 32 Drain Hose / Water Tank 0.8gal (3L) Rotary Postary Postary 8½ feet 4½ inch 62 / 70½ 22% x 18% x 11 35 x 215% x 13% FedEx / UPS	Rated Current (Cooling/Heating)	9.1 A / 13.6 A	
Operating Outdoor Temperature Refrigerant Refrigerant Water Drainage Drain Hose / Water Tank Water Tank Capacity Compressor Type Rotary Power Cord Length Cooling Hose Diameter Weight (Net/Gross) lbs Product Dimensions without Hose (HxWxD) inch Package Dimensions (HxWxD) inch Type of Shipping P 32 Rotary 0.8gal (3L) Rotary 8½ feet 4½ inch 4½ inch 22½ x 18½ x 11 35 x 21½ x 13½ FedEx / UPS	Noise Level	55 dB	
Refrigerant Water Drainage Drain Hose / Water Tank Water Tank Capacity Compressor Type Rotary Power Cord Length Cooling Hose Diameter Weight (Net/Gross) lbs Product Dimensions without Hose (HxWxD) inch Package Dimensions (HxWxD) inch Type of Shipping R 32 Drain Hose / Water Tank 0.8gal (3L) Rotary 8½ feet 4½ inch 62 / 70½ 22% x 18% x 11 35 x 215/16 x 13% FedEx / UPS	Indoor Temperature (Cooling/Heating)	50°F - 99°F	
Water Drainage Water Tank Capacity Compressor Type Power Cord Length Cooling Hose Diameter Weight (Net/Gross) lbs Product Dimensions without Hose (HxWxD) inch Package Dimensions (HxWxD) inch Type of Shipping Drain Hose / Water Tank 0.8gal (3L) Rotary 8½ feet 4½ inch 62 / 70½ 22½ x 18½ x 11 35 x 21½ x 13½ FedEx / UPS	Operating Outdoor Temperature	23°F - 131°F	
Water Tank Capacity Compressor Type Power Cord Length Cooling Hose Diameter Weight (Net/Gross) lbs Product Dimensions without Hose (HxWxD) inch Package Dimensions (HxWxD) inch Type of Shipping O.8gal (3L) Rotary 8½ feet 4½ inch 62 / 70½ 22% x 18% x 11 35 x 215% x 13% FedEx / UPS	Refrigerant	R 32	
Compressor Type Power Cord Length Cooling Hose Diameter Weight (Net/Gross) Ibs Product Dimensions without Hose (HxWxD) inch Package Dimensions (HxWxD) inch Type of Shipping Rotary 8½ feet 4½ inch 62 / 70½ 22% x 18% x 11 35 x 21% x 13% FedEx / UPS	Water Drainage	Drain Hose / Water Tank	
Power Cord Length Cooling Hose Diameter Weight (Net/Gross) lbs Product Dimensions without Hose (HxWxD) inch Package Dimensions (HxWxD) inch Type of Shipping 8½ feet 4½ inch 62 / 70½ 22½ x 18⅓ x 11 35 x 21⁵⁄₁6 x 13¾ FedEx / UPS	Water Tank Capacity	0.8gal (3L)	
Cooling Hose Diameter Weight (Net/Gross) lbs Product Dimensions without Hose (HxWxD) inch Package Dimensions (HxWxD) inch Type of Shipping 4½ inch 62 / 70½ 22% x 18% x 11 35 x 21% x 13% FedEx / UPS	Compressor Type	Rotary	
Weight (Net/Gross) lbs $62 / 70 \%$ Product Dimensions without Hose (HxWxD) inch 22% x 18% x 11Package Dimensions (HxWxD) inch 35 x 21% x 13% Type of ShippingFedEx / UPS	Power Cord Length	8½ feet	
Product Dimensions without Hose (HxWxD) inch Package Dimensions (HxWxD) inch Type of Shipping 22% x 18% x 11 35 x 215% x 13% FedEx / UPS	Cooling Hose Diameter	4½ inch	
Package Dimensions (HxWxD) inch 35 x 21% x 13% Type of Shipping FedEx / UPS	Weight (Net/Gross) lbs	62 / 70½	
Type of Shipping FedEx / UPS	Product Dimensions without Hose (HxWxD) inch	22% x 18% x 11	
	Package Dimensions (HxWxD) inch	35 x 21⁵⁄₁6 x 13¾	
Control of the contro	Type of Shipping	FedEx / UPS	
	Certification	ETL	
Warranty 1 Year on Parts and Labor	Warranty	1 Year on Parts and Labor	

Keywords: Indoor/Outdoor Mobile Spot Cooler, Garden Cooler, Commercial Store Cooler, Tiny Home Cooler, Room Cooler,

Cabin Cooler Residential Air conditioner Mobile Spot,

I/O Residential Portable, I/O Spot Air conditioner with twin duct





Equator Advanced Appliances • 10222 Georgibelle Drive, Suite 200 • Houston, TX 77043-5249

Toll Free: 800-935-1955 • Fax: 832-202-2732 • www.EquatorAppliances.com • E-Mail: mail@equatorappliances.com

Document#: WSSEQOAC400004052024