A ½" knockout for conduit feed or sensors included for easy installation



Create an asymmetric up/down fan distribution while maximizing lumens



| Ordering Information Ex. OWCF4N1036MV50BZ | | | | | | |
|-------------------------------------------|-------------------|-----------------------|-----------------|---------------------|-------------------|--------------------|
| Series | Distribution | Version | Wattage | Voltage | CCTs | Finish |
| OWCF4 | N (Narrow) | 10 (Version 1) | 36 (36W) | MV (120-277) | 30 (3000K) | BZ (Bronze) |
| | | | | | 40 (4000K) | WH (White) |
| | | | | | 50 (5000K) | |

DORADO - OWCF | LED Wall Mount Fan

The Dorado Fan Square LED Wall Mount Cylinder features an attractive, contemporary design while maximizing lumen output. The Dorado Fan uses convex lenses to create asymmetric up/down fan light distribution. The fixture features a detachable mounting plate for easy universal mounting to junction boxes.

- Die-cast aluminum housing with detachable mounting plate
- Easy to use mounting plate allows for quick mounting to J-Boxes
- 1/2" knockout for conduit wiring
- Tempered glass, convex lenses create asymmetric up/down fan distribution
- 3000K, 4000K, and 5000K CCTs
- 120-277VAC
- Available in 34.4 watts



Applications: Porches, walls, columns, office spaces, restaurants, clubs, walkways and other residential or commercial spaces.

Dorado - OWCF Quick Reference Guide

Lm W Lm/W 1387 35 40-46

CCT







FINISH Prop 70 White



