

Intrinsic

Recessed housing Mounted • Damp Location Listed PROGRESS LED



Description:

Intrinsic 5" / 6" 5-CCT LED Eyeball (P851-ICAT/P1851-ICAT/P1841-ICAT/P87-AT/P87-ATQC/P187-TG/P86-TG/P186-TG/P821-FBFC/P821-FB/P871-LED/P1871-LED)

Specifications:

- Dimmable to 10% brightness (See Dimming Notes)
- 6 in of wire supplied

Performance:

| | |
|------------------------|------------------------------------|
| Number of Modules | 1 |
| Input Power | 8 W |
| Input Voltage | 120 VAC |
| Input Frequency | 60 Hz |
| Lumens/LPW (Delivered) | 750/93 (LM-79) |
| CCT | 2700 K |
| | 3000 K |
| | 3500 K |
| | 4000 K |
| | 5000 K |
| CRI | 90 CRI |
| Life (hours) | 50000 (L70/TM-21) |
| EMI/RFI | FCC Title 47, Part 15, Class B |
| Warranty | 5-year Limited Warranty |
| Labels | cCSAus Damp Location Listed |
| | ENERGY STAR® qualified |
| | Meets California Title 24 JA8-2016 |

P800018-028-CS



Dimensions:

Length: 7-11/16 in
 Diameter: 7-11/16 in
 Height: 3-15/16 in



The adjustable light source can be aimed allowing the trim to be used as a standard downlight, accent light, wall wash or sloped ceiling light.

P800018-028-CS

Dimming Notes:

P800018-028-CS is designed to be compatible with many Triac/Forward Phase ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls:

Eaton AAL06

Eaton SAL06P

IDevelop IDEV009

Leviton_Trimatron 6681

Leviton IPI06-1LZ

Leviton 6672

Leviton 6674

Lutron NTEVL-300

Lutron DVELV-300P

Lutron Caseta Wireless

Lutron AYCL-153P

Lutron SCL-153P

Lutron TGCL-153-PH-WH

Lutron MACL-153M

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.

Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.