# QDL22150

PowerPact Q - molded case circuit breaker - 2pole - 25 kA - 240 V - 150 A





NΛ	21	n
IVI	aı	

Product or component type	Circuit breaker	
Range of product	PowerPact Q	
Trip unit technology	Thermal-magnetic	

Complementary

Line Rated Current	150 A
[Ue] rated operational voltage	240 V AC
Number of poles	2
Breaking capacity	25 kA 240 V AC
Continuous current rating	80 %
Breaking capacity code	D
Mounting mode	Unit mount
Electrical connection	Lugs load AWG 4300 kcmil aluminium/copper Lugs line AWG 4300 kcmil aluminium/copper
Magnetic hold current	1200 A
Magnetic tripping current	2400 A
Maximum Height	6.47 in (164.34 mm)
Maximum Width	4.5 in (114.30 mm)
Maximum Depth	3.93 in (99.82 mm)
Tightening torque	247.82 lbf.in (28 N.m) 0.040.23 in² (25150 mm²) AWG 4300 kcmil)

#### **Environment**

Product certifications	UL Listed IEC CSA
	CSA

### Ordering and shipping details

Discount Schedule         DE2A           GTIN         00785901412595           Nbr. of units in pkg.         1           Package weight(Lbs)         3.32 lb(US) (1.51 kg)           Returnability         Yes	Category	00005 - QO,Q2L 2P ENCL & BREAKERS
Nbr. of units in pkg. 1 Package weight(Lbs) 3.32 lb(US) (1.51 kg)	Discount Schedule	DE2A
Package weight(Lbs) 3.32 lb(US) (1.51 kg)	GTIN	00785901412595
	Nbr. of units in pkg.	1
Returnability Yes	Package weight(Lbs)	3.32 lb(US) (1.51 kg)
	Returnability	Yes
Country of origin MX	Country of origin	MX

## **Packing Units**

Unit Type of Package 1	PCE
Package 1 Height	4.90 in (12.446 cm)
Package 1 width	6.20 in (15.748 cm)
Package 1 Length	9.80 in (24.892 cm)
Unit Type of Package 2	PAL
Number of Units in Package 2	729
Package 2 Weight	2530.00 lb(US) (1147.588 kg)
Package 2 Height	40.00 in (101.6 cm)
Package 2 width	40.00 in (101.6 cm)
Package 2 Length	48.00 in (121.92 cm)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: DIDP and DINP which is known to the State of California to cause Carcinogen and Reproductive harm. For more information go to www.p65warnings.ca.gov
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EEU RoHS Declaration
Mercury free	Yes
RoHS exemption information	€Yes
China RoHS Regulation	<sup>™</sup> China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
PVC free	Yes
Halogen content performance	Halogen free product

#### Contractual warranty

Warranty	18 months	