



The Building Blocks™ Wood line provides the warmth and sophistication of wood in a durable porcelain tile. Designed to blend perfectly with other Building Blocks™ products, this line provides a stylized re-creation of natural elements that create a harmonious blend of textures and sizes.

BUILDING BLOCKS™ WOOD | OAK

Glazed Porcelain



Gray

Sizes

8"x47"

7.76"x46.89"

Thickness

10mm

Faces

40

Finish

Matte

Edge

Rectified

Grout Joint Recommendation

3/16"

Testing	Abrasion Resistance C1027	Breaking Strength C648	Chemical Resistance C650	Water Absorption C373	DCOF ANSI A137.1	Scratch Hardness MOHS	Shade Variation Rating
Results*	IV	>650 lbf	Resistant	<0.50%	>0.50	6	V2

Product and Installation Details | ANSI A108.02

Section 4.3.8.2 - For running bond/brick joing patterns utilizing tiles (square or rectangular) where the side being offset is greater than 18" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the tile manufacturer. If an offset greater than 33% is specified, specifier and owner must approve mock-up and lippage.

Recommended 33% Offset



*For more information visit www.emser.com. Always consult a professional for proper usage and installation.

