



Folding, Rechargeable

Slim Bar LED Work Light



The NextLED **Folding, Rechargeable Slim Bar LED Work Light** has a slim, compact design that allows you to illuminate tight spaces. It features a new, universal swivel and rotating light bar so you can locate light exactly where you want it. And with the simple push of a button, you can easily cycle between 3 convenient light sources. It provides both 155 and 500 lumen light and also a convenient 65 lumen spot light located at the tip of the bar. Its designed with a comfortable non-slip grip that features a strong, magnetic base so you can affix the light to most metallic surfaces, giving you convenient hands-free use.

CAUTION:

Read all instructions and warnings before operating!
SAVE THESE INSTRUCTIONS!

WARNING: To avoid serious injury or death from electrical shock or fire:

1. This fixture **MUST ALWAYS BE USED IN ACCORDANCE WITH ALL ELECTRICAL AND SAFETY CODES AND ORDINANCES**, including the most recent National Electric Code (NEC) and with the Occupational Safety and Health Act (OSHA) Volume 1 on General Industry Standards and interpretations.
2. **ALWAYS** make certain that the power source conforms to the rating on the fixture.
3. **DO NOT** inspect or service the fixture while charging.
4. **CAUTION:** This fixture is for indoor use. Keep dry. Do not open, drop, short-circuit, incinerate, expose to temperatures higher than 140°F, or charge/use if damaged.
5. People with pacemakers should consult their physician(s) before use. Electromagnetic fields in close proximity to heart pacemaker could cause pacemaker interference or pacemaker failure.
6. This fixture is not explosive-proof, **DO NOT** use in potentially dangerous locations, such as in flammable or explosive atmospheres.
7. **NEVER** operate the light with the clear protective glass broken or removed.
8. **NEVER LOOK DIRECTLY INTO LIGHT SOURCE.** LED's are extremely bright and can damage eyes with prolonged exposure.
9. **KEEP AWAY** from heating vents, radiators, or other sources of heat.
10. **KEEP OUT OF REACH OF CHILDREN.**

LITHIUM BATTERY SAFETY WARNINGS

LITHIUM BATTERIES STORE A LARGE AMOUNT OF ENERGY AND WILL VENT FIRE OR EXPLODE IF MISTREATED:

1. Keep work light dry.
2. **DO NOT DO ANY OF THE FOLLOWING TO COLOR MATCH LIGHT:**
 - a. Drop
 - b. Open
 - c. Short-circuit
 - d. Puncture
 - e. Incinerate
 - f. Expose to temperatures greater than 140°F.
3. Charge Color Match Light only according to these instructions

OPERATION/CHARGING

1. To Turn Light On:

Press the power button once for 500 lumen lighting. Pressing the power button a second time will change the light to 155 lumens. Press the power button a third time to turn on the 65 lumen spot light. Pressing a fourth time will turn the light off.

2. Battery Charging:

WARNING: YOU MUST FULLY CHARGE THE BATTERY BEFORE USING THE SLIM BAR LED WORK LIGHT FOR THE FIRST TIME!

Use the USB-C charging cable that came with this product. Plug one end into the port located under the rubber cover on the back of the light bar handle. Plug the other end into a 120V power outlet. The charging indicator light (on the charging port) will be red when not fully charged and while charging. The charging indicator light will turn green when the unit is fully charged. Disconnect the USB cord and the Slim Bar LED Work Light is ready for use.

To prolong the life of the battery, it is best to recharge the battery before it is fully discharged.

Avoid extreme temperatures, especially heat.

DO NOT attempt to open the battery compartment as this could damage the unit and void the warranty.

WARNING! Charge while indoors only.

WARNING! Always use the provided charging cable and charging base. Using a non-compatible cable and charger could cause damage to the Slim Bar LED Work Light or personal injury.

MAINTENANCE

Only qualified service personnel must perform repairs. Opening or visible attempts to open or repair work light will void any warranty and/or cause damage to the product or personal injury.

CAUTION! Do not use solvents such as gasoline, turpentine, etc. to clean the unit. Aerosols and other chemical will fog the clear polycarbonate lens.

ONE YEAR LIMITED WARRANTY

If this NextLED® product fails due to defect in materials or workmanship, NextLED® will at its option, repair it or replace it with the same or comparable model, free of charge.

For repair or replacement under warranty, return to the retail establishment where the product was purchased.

This warranty give you specific legal rights and you may have other rights that vary from state to state.

This warranty is void if damage or defect has resulted from accident, abuse, misuse or faulty repair. In no event will NextLED® be liable for any consequential, special, incidental, or indirect damages of any kind arising out of the use or misuse of this product.

Maximum liability shall not in any case exceed the purchase price of the product including shipping. Some states do not allow the exclusion or limitation of incidental or consequential damages so the above exclusions or limitations may not apply to you.

SPECIFICATIONS

Run Time

500 lm flood light..... 2.5 hrs.
155 lm flood light..... 7.5 hrs.
65 lm spot light..... Up to 20 hrs.

Beam Distance

High mode flood light.. 95 ft.
Low mode flood light... 50 ft.
Spot light..... 30 ft.

Brightness

High mode flood light.. 500 lm
Low mode flood light... 155 lm
Spot light..... 65 lm

Charging Time 4 hrs.

Power 3.7V, 2200 mAh
Rechargeable
18650 Lithium-Ion

Charger 5VDC/2A

Cable USB-C (included)

Protection Rating IPX4

Your product, accessories and packaging should be discarded in an environmentally responsible way.

Illustrations, figures and photos may vary slightly due to our program of continuous product improvements.

Cancer and Reproductive Harm
www.P65Warnings.ca.gov



© 2026 Distributed by Nextool Inc.
Schaumburg, IL
Visit www.mynextled.com
Customer Service: 1-877-886-6822
MADE IN CHINA



Scan to register your product

Simply scan and register
your product for warranty
or visit www.mynextled.com.