

## PROMARK™ CARE & MAINTENANCE

### CARE & MAINTENANCE

Proper care, maintenance and installation play a key role in the performance of Armstrong Flooring floors. Installation and maintenance guidelines can be found on [www.FloorExpert.com](http://www.FloorExpert.com) or by calling 1-800-233-3823.

To keep the lasting shine and fresh feel of your investment for as long as possible, we recommend that you:

#### Do

- Wipe up spills as soon as possible. Never use highly abrasive scrubbing tools on any resilient floor.
- Wash occasionally with Armstrong® Flooring Once 'n Done® Resilient Floor Cleaner.

#### Don't

- Use detergents, abrasive cleaners or "mop and shine" products – they may leave a dull film on your floor.
- Use paste wax or solvent-based polishes.
- Use rolling casters as they can damage the floor.
- Use a beater bar when vacuuming because it can visibly damage the floor surface.
- Use highly abrasive scrubbing tools.

### Proactive protection for your floor

- When moving appliances or heavy furniture, lay a plywood panel on your floor and "walk" the item across it. This protects your floor from scuffing and tears.
- Use floor protectors on furniture to reduce indentation. As a general rule, the heavier the item, the wider the floor protector needed.
- Place a walk-off mat at outside entrances to reduce the amount of dirt brought into your home. We do not recommend the use of rubber- or latex-backed mats (except where noted) because the chemical (antioxidant) they often contain can permanently stain your floor. We suggest a non-staining vinyl-backed mat or a woven rug that is colorfast.
- All Armstrong floor care products have been specifically developed to care for Armstrong floors.

### Immediately after installation

- Maintain a minimum room temperature between 65 and 85 degrees Fahrenheit for 48 hours before, during and after installation is completed, then maintain temperatures between 55°F (13°C) and 85°F (29°C) thereafter. *Rigid Core Vantage* can be installed in fully-enclosed three-season rooms where the expected temperature range is 32°F (0°C) to 100°F (38°C) after installation is complete.
- We recommend that you do not scrub or wash your floor for five days.

### Application Guidelines for Armstrong Flooring Residential Products

WEAR LAYER THICKNESS	MAXIMUM LEVEL OF FOOT TRAFFIC	APPLICATIONS	AREAS IN APPLICATION
6 mil	Residential	Residences	Homes and multifamily residences