

DETAILED SPECIFICATIONS AND COMPONENTS

EGS107501G2K25

Max Amperage	30 A
Voltage	240
Max Wattage	7,500
Number of Circuits	10
Dimensions	20.5 x 11.5 x 14.5 in



EGSPI30

Max Amperage	30 A
Voltage	120/240
Max Wattage	7,500
Dimensions	6.75 x 4.25 x 4.13 in
NEMA	L14-30 INLET



HEPC3025

Max Amperage	30 A
Length	25'
NEMA	14-30P to 14-30R




MODEL


EGS107501G2K25

DETAILED SPECIFICATIONS AND COMPONENTS

**CONNECTICUT
ELECTRIC**
MANUFACTURING
A VITAL ELECTRIC SUPPLY COMPANY



QTY: 6
W6 MINI-BREAKER 15 AMP
MODEL: EGSFHW615A



ROCKER SWITCH
MODEL: EGS20RSA



QTY: 2
W6 MINI-BREAKER 20 AMP
MODEL: EGSFHW620A



2500 EGS WATT METER
MODEL:
EGS3750WMNS

- MULTI-CIRCUIT CAPABILITY
- DOUBLE-THROW ROCKER SWITCH
- FOR USE WITH 120/240 VOLT GENERATORS RATED UP TO 30 AMPS
- NEMA 3R RAINPROOF RATING
- INDOOR/OUTDOOR USE
- POWDER-COATED, RUST-PROOF STEEL ENCLOSURE
- 7500 WATTS

MODEL

EGS107501G2