

INSTALLATION AND SAFETY INSTRUCTIONS

FOR YOUR SAFETY

WARNING: BE SURE THE ELECTRICITY TO THE WIRES YOU ARE WORKING ON IS SHUT OFF: EITHER THE FUSE IS REMOVED OR THE CIRCUIT BREAKER IS SHUT OFF
CAUTION: THE PRODUCT SHOULD BE INSTALLED BY A QUALIFIED ELECTRICIAN THAT IS AWARE OF THE CONSTRUCTION AND OPERATION OF THE PRODUCT AND THE HAZARDS INVOLVED

GENERAL

You don't need special tools to install this fixture
Be sure to follow the steps in the order given. Under no circumstances should a fixture be hung on house electrical wires nor should a swag type fixture be installed on a ceiling, which contains a radiant type heating system. Read instructions carefully
If you are unclear as to how to proceed, consult a qualified electrician

NOTE: Proper wiring is essential for the safe operation of this fixture

FIXTURE ASSEMBLY

Carefully removed the fixture from the carton and check that all parts are included as shown in figure. Be careful to misplace any of the screws or parts, which are needed to install this fixture

INSTALLATION

Please note that small soft pads include in the parts bag, if needed, please attach the small soft pad on the cage tab before assembling the Glass panel into the fixture cage.

STEP 1: Insert the Glass Panel (J) into the slot in the top edge of the cage (I)
Secure the Glass Panel (J) by pressing the tabs on the bottom of the cage the tabs should be bent up as possible to hold the Glass panel tight.

STEP 2: Attach the mounting strap (C) to the outlet box (A) by using two mounting screws (D)

STEP 3: Attach the canopy (F) to the mounting strap and secure it with the collar loop (E)

STEP 4: Connect the metal chain to the loop on fixture and the collar loop on canopy by using open link (G)

STEP 5: Loosen the collar loop ring to allow the canopy slide down along with Chain, Weave the fixture wire (H) through metal chain up into the outlet box (A)

STEP 6: Pull out the source wires from the outlet box (A)

Make wire connections using wire nuts (B) as follow

-Connect the smooth wire (printing marks) from the fixture to the black wire from the power source; Connect the ribbed wire (unmarked) from the fixture to the white wire from the power source.

Attach the fixture grounding wire (usually green insulation or bare wire) to the mounting plate with the green grounding screw (C), and then connect it to the house grounding wire with wire nut (B).

Carefully put the wires back into the outlet box

STEP 7: Rising up the canopy (F) to cover the outlet box, then, secure it with the collar loop ring.

STEP 8: Insert the bulb (K) onto the socket and screw snugly Into place
Your fixture is now assembled and ready to use. (the bulb not included)
See relamping label at socket area or packaging for maximum allowed wattage

CLEANING

To clean, Wipe fixture with a soft and dry cloth.
Do not use abrasive materials such as scouring pads or powders, steel wool or abrasive paper.

Line art shown may not exactly match the fixture enclosed.
However, the installations do apply to this fixture
ITEM NO: 2687-PBK ,2687-PBZ

