



INTRODUCING OWENS CORNING® **THERMAFIBER®** **FIRE & SOUND GUARD® PLUS** **SOUND AND THERMAL BATT**



Thermafiber® Fire & Sound Guard® Plus is a hybrid light-density mineral wool batt that is designed to use in both interior and exterior wall cavities. This product combines the attributes of Thermafiber® UltraBatt™ and Thermafiber® Fire & Sound Guard® into one product, saving time for the installer.



Thermal Comfort

Contributes to energy efficiency with R-values that won't decrease as the insulation ages.



Fire Resistant

Mineral wool is naturally fire resistant



Non-Combustible

Mineral wool is non-combustible per ASTM E136.



Mold Resistant

Resists mold, fungi and is vermin-resistant due to its being an inorganic material - tested per ASTM C1338.



Sound Control

Helps control noise between floors, through walls, and from outdoors.



Ease of Installation

Batt product that is easy to cut and install, flexibility and durability allow it to conform and friction fit.



Recycled Content

70% recycled content.



Availability

Available in a wide range of R-values for common wood stud assemblies as well as steel framing in both narrow and wide widths.

- **Wood Stud R-Values**
R-11, R-13, R-15, R-21, R-23, R-30
- **Steel Stud R-Values**
R-10, R-11, R-13, R-15, R-21, R-24

Learn more by visiting
[owenscorning.com/thermafiber](https://www.owenscorning.com/thermafiber)

THERMAFIBER, INC.
ONE OWENS CORNING PARKWAY
TOLEDO, OH 43659 USA

888-TFIBER1 [834-2371]
www.owenscorning.com/thermafiber

Pub. No. 10025708-B. Printed in U.S.A. August 2025.
© 2025 Owens Corning. All Rights Reserved.
© 2025 Thermafiber, Inc. All Rights Reserved.