

WARNING: FLAMMABLE.
VAPOR HARMFUL.
See other cautions on the back panel.
10.5 fl. oz. (310 mL)

Seals everything that goes

Through the ROOF!

sticks to
WET
surfaces

sashco
Products That Work
Clear

- Apply down to 0°F (-18°C)
- Easy to gun
- Lasts 20x longer than asphalt roof cements

Seals Leaks That Asphalt Can't!

Actual customer reviews: "Worked like a charm", "Yes, it is the best", "Would buy again & again". Through the Roof!® will immediately seal your nagging roof leaks even if it rains before, during or after application. You can apply it to wet surfaces & in freezing temperatures. It dries crystal clear & remains highly elastic for a permanent seal.

- Expands & contracts with temperature changes
- Stays elastic, won't dry hard or crack
- Excellent UV resistance
- Meets FHA requirements & ASTM C794

Through The Roof! sticks to most surfaces*

- Galvanized metal & aluminum flashing
- PVC, ABS vent pipe, skylights
- Gutters & downspouts, ductwork & vents
- Cement, slate & other roof tile
- Chimneys, brick, block, mortar
- Shingles, shakes, tiles
- Asphalt roof cement, acrylic roof coatings

Through the Roof! is also available in brush-grade quarts & gallons.

* Applying on thin rubber membranes, such as EPDM, may cause warping. Test in an inconspicuous area prior to use.

APPLICATION RANGE: Surface temperatures of 0° to 120°F (-18° to 49°C)

SERVICE RANGE: -25° to 180°F (-34° to 82°C)

DIRECTIONS FOR USE

1. Close ventilation intakes on roof until solvent dissipates (approx. 12 hours).
 2. Surfaces must be clean & free of frost, loose materials, dust, etc. Remove any silicone with a silicone caulk remover.
 3. Insert backer rod into joints deeper than 1/2" to provide proper sealant depth & a stronger, longer-lasting seal.
 4. Cut tip at 45° angle. Puncture inner seal. Use caulk gun.
 5. Tool for a smoother bead using a caulking tool or soapy finger & a light, skimming touch.
- NOTE: Flammable during early cure (approx. 24-48 hours).
Fully cured in 1-2 weeks. Paintable after 1 week.

CLEAN-UP & STORAGE

- Clean tools & unwanted surface spills with mineral spirits. Clean hands with citrus-based hand cleaners.
- To store, wrap nozzle tightly with plastic wrap & a rubber band.

WARNING: VAPOR HARMFUL. FLAMMABLE. Do not breathe fumes. Do not swallow. Do not use near heat, sparks or flames. Do not smoke. Do not get in eyes. Do not get on skin. KEEP OUT OF REACH OF CHILDREN. Wear safety glasses and chemical resistant gloves. Use only in a well-ventilated area. Contains petroleum distillates and toluene.

FIRST AID: If swallowed, call a Poison Control Center or doctor immediately. Do not induce vomiting. If in eyes, rinse with water for 15 minutes. If on skin, rinse well with water. If breathed in, move person into fresh air.

⚠ WARNING: This product can expose you to toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

VOC: 380 g/L, 43% by wt.

LIMITED LIFETIME WARRANTY: For a detailed description of the warranty & exclusions, visit www.sashco.com.

sashco
Products That Work®

CE

©2017 Sashco Inc.
10300 E. 107th Place • Brighton, CO 80601
800-767-5656 • www.sashco.com
Made in USA



TRFCTG11-17 0