

KOHLER®

Roughing-In

K-1148-H PROFLEX® 7242 OVAL BATH WHIRLPOOL WITH HEATER

Product Information

Applicable products:				
Bath whirlpool – drop-in			K-1148-H	
Fixture*:				
Bathing well:				
Basin area, bottom		53'' (1346 mm) x 26'' (660 mm)		
Basin area, top		65'' (1651 mm) x 34'' (864 mm)		
Weight		79-1/4 lbs (35.9 kg)		
To overflow:				
Water depth		15'' (381 mm)		
Capacity		78 gal (295.3 L)		
* Approximate measurements for comparison only.				
Pump:		V	HZ	A
1-speed		120	60	7.5
Heater:	kW	V	Hz	A
	1.5	120	60	12.5
Included components:				
Cut-out template			114861-7	

Required Electrical Service

Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI):

Pump/control 120 V, 15 A, 60 Hz

Heater 120 V, 15 A, 60 Hz

Locate the outlet behind the whirlpool and within 24" (610 mm) of the pump.

Installation Notes

Install this product according to the installation guide.

Floor support under whirlpool must provide for a minimum of 36 lbs/square foot (176 kg/square meter) loading.

This fixture conforms to ANSI Standard Z124.1.2. All dimensions are nominal.

No change in measurements with drain shown. (K-11677 or K-11677-M)

