# Pro 340 Consumer Fire Extinguisher

Part number 21005782 Multipurpose use

## Rechargeable

#### UL Rated 3-A, 40-B:C



For use on the following types of fire:



## Product Specification

## Description

Suitable for use on Class A (trash, wood & paper), Class B (liquids & gases) and Class C fires (energized electrical equipment).

The PRO 340 is fitted with a pressure gauge that provides at-a-glance status, is manufactured from lightweight aluminum cylinder with a tough aluminum valve assembly.

Features bilingual nameplate and carton.

#### FOR MODERATE HAZARDS

A 3-A:40-B:C rated extinguisher is required for protecting MODERATE hazard occupancies such as: home garage & workshop, light manufacturing, dining areas, auto showrooms, parking garages & storage areas.

## Features

- **Multipurpose Fire** Extinguisher
- Aluminum cylinder
- Tough aluminum valve assembly
- Pressure gauge allows for immediate pressure status check
- Rechargeable unit.
- Assembled in Mexico from global components
- 6 year warranty
- UL rated 3-A:40-B:C
- UL approved wall hanger
- Coast Guard (U.S.C.G) approved when fitted with optional mounting bracket
- Powder coated cylinder for corrosion protection
- Optional metal strap bracket Pt # 466400



Pt # 21005782 - 4 pack UPC: 0-47871-05782-5 I2F - 10047871057822

#### Packaging Options



Net agent weight (Average) 5.5 lb. Unit weight (Average) 9.0 lb. Diameter 4.5 inches Height 16.5 inches MASTER PACK 13-15 seconds Discharge time Discharge range 10-15 feet Operating pressure 195 psi Packaging dimensions (inches) Cylinder Seamless aluminum Depth Valve/handle/lever 4.75 Aluminum Carton Strap Bracket (not supplied) U.S.C.G approved Master Pack 13.0



Height

17.0

9 87

Width

17 25

6.0

Kidde Residential and Commercial Division

1016 Corporate Park Drive, Mebane, NC 27302 • Tel. 1.800.880.6788 • www.kidde.com