

WEATHERPROOF WHILE-IN-USE COVER SERIES INSTALLATION INSTRUCTIONS

WHILE -IN-USE COVER DESCRIPTION.

This product is a weatherproof cover that is intended to enclose an electrical device (Duplex, GFCI and 1 3/8" round) (Deep Cover also for use with 1 9/16" round) and protect the device from inclement weather even when a plug and cord are inserted in it. It is designed to install quickly and easily (see instructions below) and provide an attractive, durable finish that will yield long lasting results.

Application

The cover should be installed in areas subject to saturation from water or other liquids. (see description for "Wet Location" and "Damp Location" in the National Electrical Code). The single gang 3 1/8" cover can be mounted either horizontally or vertically as long as the hinge is in the top corner. See Figure 1 (A-B) for applicable mounting and attachment options. See Figure 2 for double gang applicable mounting and attachment options. The cover includes multiple inserts, so it can be used to cover different types of electrical devices.

WARNING - Turn off all power to circuit before installing this device. Improper wiring of any electrical device can cause serious injury or death. These wiring devices should only be installed by an Electrician or other qualified person.

CAUTION - This cover should be installed in accordance with the National Electrical Code, and all applicable local codes and standards.

INSTALLATION INSTRUCTIONS

NOTE: The cover should be installed on a smooth, flat, non-porous surface. To install on an irregular surface, use a proper amount of caulking to ensure a watertight seal between the back of the cover and the mounting surface.

1. Disconnect power to circuit by removing fuse or turn breakers to OFF before installing.
2. Remove the existing receptacle cover, if any, and discard.
3. Back off the mounting screws that hold the GFCI or receptacle to the junction box but do not remove screws.
4. Place the cover on the box while mounting screws come into the cover through the keyhole, and slide the assembly to left. (see Figure 3).

Center the device in the box. Tighten screws.

5. If mounting to an FS or outdoor junction box use the four screws provided to further secure the assembly to the box.
6. DO NOT OVER TIGHTEN SCREWS.
7. Choose appropriate insert and snap in by putting one long edge in place first and rotating the plate over the device. (If device is in the way, loosen screws and move left or right). Discard other Insert (s).
8. For best rain protection, be sure to route cords through the cord outlet and press the cover firmly until it snaps closed.

Figure 1. (A) Single gang 3 1/8" Vertical




Figure 1. (B) Single gang 3 1/8" Horizontal




Figure 1. (C) Single gang 4 1/2"




Figure 2. Double gang




Figure 3