

## Safety Data Sheet

#### **SECTION 1: Identification**

1.1. Identification

Product name : Innocare B580

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Water-dilutable surface cleaner for use according to the user instructions.

1.3. Details of the supplier of the safety data sheet

Zahav LLC dba Clean My Steel

20423 State Rd. 7 Boca Raton, FL 33498

1.4. Emergency telephone number

Emergency number : 561-410-3636

## SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

#### **GHS US classification**

Flam. Liq. 3 H226 Eye Irrit. 2 H319

Full text of hazard classes and H-statements : see section 16

### 2.2. Label elements

#### **GHS US labeling**

Hazard pictograms (GHS US)





GHS02 GHS07

Signal word (GHS US) : Warning

Hazard statements (GHS US)

: H226 - Flammable liquid and vapor
H319 - Causes serious eye irritation

Precautionary statements (GHS US) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P233 - Keep container tightly closed.

P240 - Ground/Bond container and receiving equipment.

P241 - Use explosion-proof electrical/ventilating/lighting equipment.

P242 - Use only non-sparking tools.

P243 - Take precautionary measures against static discharge. P264 - Wash hands, forearms and face thoroughly after handling.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse

skin with water/shower.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P337+P313 - If eye irritation persists: Get medical advice/attention. P370+P378 - In case of fire: Use media other than water to extinguish.

P403+P235 - Store in a well-ventilated place. Keep cool.

P501 - Dispose of contents/container to hazardous or special waste collection point, in

accordance with local, regional, national and/or international regulation.

## 2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

### **SECTION 3: Composition/Information on ingredients**

#### 3.1. Substances

Not applicable

01/02/2020 EN (English US) Page 1

## Safety Data Sheet

#### 3.2. Mixtures

Name	Product identifier	%	GHS US classification
Ethyl alcohol	(CAS-No.) 64-17-5	1 – 5	Flam. Liq. 2, H225 Carc. 1A, H350
Poly(oxy-1,2-ethanediyl), .alphasulfoomegahydroxy-, C12-14-alkyl ethers, sodium salts	(CAS-No.) 68891-38-3	1 – 5	Skin Irrit. 2, H315 Eye Dam. 1, H318

Full text of hazard classes and H-statements : see section 16

#### **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

First-aid measures after inhalation : Supply fresh air.

First-aid measures after skin contact : Wash affected areas with soap and water and rinse well. Take off all contaminated clothing and

wash it before reuse.

First-aid measures after eye contact : Rinse immediately carefully and thoroughly with eye-bath or water.

First-aid measures after ingestion : Wash out mouth with water and drink plenty of water. Do not induce vomiting.

#### 4.2. Most important symptoms and effects, both acute and delayed

No additional information available

#### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

## **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

Suitable extinguishing media : Water jet, alcohol-resistant foam, carbon dioxide, extinguishing powder.

Unsuitable extinguishing media : Full water jet.

#### 5.2. Special hazards arising from the substance or mixture

Fire hazard : Flammable liquid and vapor.

Explosion hazard : None known.

Reactivity : The product is non-reactive under normal conditions of use, storage and transport.

### 5.3. Advice for firefighters

Protection during firefighting : Firefighters should wear full protective gear.

### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Avoid contact with eyes, skin and clothing.

### 6.1.1. For non-emergency personnel

No additional information available

#### 6.1.2. For emergency responders

No additional information available

#### 6.2. Environmental precautions

Avoid release to the environment.

## 6.3. Methods and material for containment and cleaning up

For containment : If possible, stop flow of product.

Methods for cleaning up : Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding

agents). Treat the recovered material as prescribed in the section on waste disposal .

#### 6.4. Reference to other sections

No additional information available

### **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling

Precautions for safe handling : Avoid contact with eyes, skin and clothing. Do not mix with other chemicals. Wear personal protection equipment (see chapter 8). When using do not eat, drink or smoke. Do not breathe

gas/fumes/vapor/spray. Use only in well-ventilated areas.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep away from ignition sources. Keep container tightly closed.

01/02/2020 EN (English US) 2/6

# Safety Data Sheet

## **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

Ethyl alcohol (64-17-5)		
ACGIH	ACGIH STEL (ppm)	1000 ppm
OSHA	OSHA PEL (TWA) (mg/m³)	1900 mg/m³
OSHA	OSHA PEL (TWA) (ppm)	1000 ppm
IDLH	US IDLH (ppm)	3300 ppm (10% LEL)
NIOSH	NIOSH REL (TWA) (mg/m³)	1900 mg/m³
NIOSH	NIOSH REL (TWA) (ppm)	1000 ppm

### Poly(oxy-1,2-ethanediyl), .alpha.-sulfo-.omega.-hydroxy-, C12-14-alkyl ethers, sodium salts (68891-38-3)

Not applicable

#### 8.2. Exposure controls

Appropriate engineering controls : General (mechanical) room ventilation is expected to be satisfactory for normal handling.

Hand protection : Nitrile rubber gloves. Eye protection : Wear safety glasses.

Skin and body protection : Wear suitable protective clothing.

Respiratory protection : If airborne concentrations are above the applicable exposure limits, use NIOSH approved

respiratory protection.

## **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Physical state : Liquid
Color : Blue
Odor : Fragrant

Odor threshold : No data available

pH : 6-7

Melting point : No data available Freezing point : No data available

Boiling point :  $100 \, ^{\circ}\text{C}$ Flash point :  $54 \, ^{\circ}\text{C}$ 

Relative evaporation rate (butyl acetate=1) : No data available Flammability (solid, gas) : No data available Vapor pressure : No data available Relative vapor density at 20 °C : No data available Relative density : No data available Specific gravity / density 1.02 g/cm<sup>3</sup> Solubility : No data available Partition coefficient n-octanol/water (Log Pow) : No data available Auto-ignition temperature : No data available

Decomposition temperature : No data available Viscosity, kinematic : No data available Viscosity, dynamic : < 10 mPa·s
Explosion limits : No data available Explosive properties : No data available Oxidizing properties : No data available

### 9.2. Other information

No additional information available

01/02/2020 EN (English US) 3/6

# Safety Data Sheet

## **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

### 10.2. Chemical stability

The product is stable at normal handling and storage conditions.

#### 10.3. Possibility of hazardous reactions

None.

#### 10.4. Conditions to avoid

None.

#### 10.5. Incompatible materials

Not determined.

### 10.6. Hazardous decomposition products

Oxides of carbon may be formed during combustion.

## **SECTION 11: Toxicological information**

## 11.1. Information on toxicological effects

Acute toxicity : Not classified

Ethyl alcohol (64-17-5)		
LD50 oral rat	7060 mg/kg	
LC50 inhalation rat (mg/l)	124.7 mg/l/4h	
ATE US (oral)	7060 mg/kg	

Skin corrosion/irritation : Not classified

Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified

Ethyl alcohol (64-17-5)	
IARC group	1 - Carcinogenic to humans
In OSHA Hazard Communication Carcinogen Yes	
list	

Reproductive toxicity : Not classified Specific target organ toxicity – single exposure : Not classified

Specific target organ toxicity – repeated

exposure

: Not classified

Aspiration hazard : Not classified

## **SECTION 12: Ecological information**

## 12.1. Toxicity

Ethyl alcohol (64-17-5)	
LC50 fish 1	12.0 – 16.0 ml/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
EC50 Daphnia 1	9268 – 14221 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 fish 2	> 100 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 2	2 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])

### 12.2. Persistence and degradability

No additional information available

### 12.3. Bioaccumulative potential

Ethyl alcohol (64-17-5)	
Partition coefficient n-octanol/water (Log Pow)	-0.32

01/02/2020 EN (English US) 4/6

## Safety Data Sheet

#### 12.4. Mobility in soil

No additional information available

#### 12.5. Other adverse effects

No additional information available

### **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

Product/Packaging disposal recommendations

 $: \ \, {\hbox{Dispose of contents/container in accordance with local/regional/national/international}} \, \\$ 

regulations.

## **SECTION 14: Transport information**

### **Department of Transportation (DOT)**

In accordance with DOT

Transport document description : UN1993 Flammable liquids, n.o.s. (Ethyl Alcohol), 3, III

UN-No.(DOT) : UN1993

Proper Shipping Name (DOT) : Flammable liquids, n.o.s.

Ethyl Alcohol

Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Packing group (DOT) : III - Minor Danger
Hazard labels (DOT) : 3 - Flammable liquid



: 203

DOT Packaging Non Bulk (49 CFR 173.xxx)
DOT Packaging Bulk (49 CFR 173.xxx)
DOT Special Provisions (49 CFR 172.102)

: B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this

subchapter are applicable.
B52 - Notwithstanding the provisions of 173.24b of this subchapter, non-reclosing pressure relief devices are authorized on DOT 57 portable tanks.

IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).

T4 - 2.65 178.274(d)(2) Normal...... 178.275(d)(3)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = 97 / 1 + a (tr - tf) Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling. TP29 - A portable tank having a minimum test pressure of 1.5 bar (150.0 kPa) may be used provided the calculated test pressure is 1.5 bar or less based on the MAWP of the hazardous materials, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx) : 150
DOT Quantity Limitations Passenger aircraft/rail : 60 L
(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 220 L

CFR 175.75)

**DOT Vessel Stowage Location** 

: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel.

Emergency Response Guide (ERG) Number : 128

Other information : No supplementary information available.

01/02/2020 EN (English US) 5/6

# Safety Data Sheet

## **SECTION 15: Regulatory information**

### 15.1. US Federal regulations

## Ethyl alcohol (64-17-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

## Poly(oxy-1,2-ethanediyl), .alpha.-sulfo-.omega.-hydroxy-, C12-14-alkyl ethers, sodium salts (68891-38-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

EPA TSCA Regulatory Flag

XU - XU - indicates a substance exempt from reporting under the Chemical Data Reporting Rule, (40 CFR 711).

### 15.2. US State regulations

Ethyl alcohol (64-17-5)				
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
Yes	Yes	No	No	

## Ethyl alcohol (64-17-5)

- U.S. Massachusetts Right To Know List
- U.S. Minnesota Hazardous Substance List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

## **SECTION 16: Other information**

#### Full text of H-phrases:

a or i i piliaooo.		
Carc. 1A	Carcinogenicity Category 1A	
Eye Dam. 1	Serious eye damage/eye irritation Category 1	
Eye Irrit. 2	Serious eye damage/eye irritation Category 2	
Flam. Liq. 2	Flammable liquids Category 2	
Flam. Liq. 3	Flammable liquids Category 3	
Skin Irrit. 2	Skin corrosion/irritation Category 2	
H225	Highly flammable liquid and vapour	
H226	Flammable liquid and vapour	
H315	Causes skin irritation	
H318	Causes serious eye damage	
H319	Causes serious eye irritation	
H350	May cause cancer	

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

01/02/2020 EN (English US) 6/6