

QC ES-6000 Specifications

Air Flow	Hi: 5,576 CFM / Low: 3,417 CFM	
HVI-916 Airflow (for CA Title 24 New Construction)	Hi: 4,040 CFM / Low: 2,450	
Recommended SQFT Coverage @ 2-3 CFM per SQFT	Covers 1,859 SQFT to 2,788 SQFT	
Energy Use	Hi: 455 Watts / Low: 112 Watts	
Amps	Hi: 5.68 / Low: 1.65	
Motor Voltage	120 VAC, 60 Hz	
# of Speeds	2	
dBA	Hi: 49.3 / Low: 38.5	
Minimum Attic Clearance	42"	
Duct Diameter	22"	
Duct Length	9 feet	
Motor Head Diameter	22 1/2"	
Motor Head Length	13 1/2"	
Dampers	Barometric Pressurized R5 Dampers	
Controls	Recommended: IT-36002 QuietCool RF Wireless Control Kit	
Warranty	10 Years	
Framing	None Required	
Joist Cutting	None Required; fits 16" or 24" on center	
Minimum Suggested Attic Venting	7.44 SQ FT net free area	
Ceiling Rough Opening	14 1/4" x 36 1/4"	
Removable Grille Outside Dimension	16" x 38"	
Shipping Weight	91 lbs.	
Box Dimensions	41" x 26" x 39"	
In The Box	<div> <div>-QC ES-6000 Motorhead</div> <div>-Ceiling Grille</div> <div>-Cut-out Template</div> <div>-Window Locks</div> </div> <div> <div>-Damper Box</div> <div>-9 Foot Duct</div> <div>-Accessory Bag</div> </div>	



For more information, visit our website at:
QUIETCOOLSYSTEMS.COM

QC ES-6000
QuietCool Energy Saver Line