FRIGIDAIRE GALLERY.

FGBM15WCVF

Available Colors : Stainless Steel

1.5 Cu. Ft. Over-The-Range Microwave with Convection

Over-The-Range Microwave

Version: 10/19



Product Specifications

Accessories

Included Accessory	Removable Metal Rack and Convection Round Rack
Certifications & Approvals	
ADA Compliant - All Brands	No
ETL Listed	No
NSF® Certified	No
Dimensions: Exterior	
Depth	15-3/4"
Height	16-3/8"
Width	29-7/8"
Dimensions: Cut-Out	
Depth (Max)	14"
Depth (Min)	12"
Height (Max)	17"
Height (Min)	16-3/4"
Width	30"
General Specifications	
Interior Light	Yes
PROP 65 Label	Yes
Turntable Material	Glass
Internal Specifications	
Microwave Interior Color	Stainless Steel
Microwave Interior Depth	13-15/16"
Microwave Interior Heigh	9-3/16"
Microwave Interior Width	20-1/4"
Capacities	
Total Capacity - Cu. Ft.	1.5
User Modes	
Child Lock	Yes - with Stop/Cancel Key

Controls	
Add 30 Seconds	Yes
Display Color	White
Display Type	LED
Electronic Clock	Yes
Numeric Touch Pad	Yes
Power Levels	High / 1 - 9
Start Button	Yes
Stop/Cancel Button	Yes
Timer Function	Yes 99:99
Touch Pad Buttons	28
Turntable On/Off	Yes - Under Settings
Electrical Specifications	
Amps @ 120 Volts	13.5
Connected Load @ 120V	1.5
Voltage Rating	120V / 60Hz
Watts @ 120 Volts	1450
Microwave Oven Controls	
Baked Potato	No
Convection Option	Yes - Convection Bake / Convection Roast
Defrost Options	Yes - Weight & Time
Keep Warm	Yes - Keep Warm @170F and Hold (Enter Time)
Melt/Soften	Yes - Melt Butter Melt Chocolate Soften Ice Cream Soften Cream Cheese
Multi-Stage Cooking	No
Popcorn	Yes - Options for 1.75/3.0/3.3 oz.
Quick Start	No
Sensor Cook Options	Yes - Bacon Frozen Dinner White Rice Frozen Breakfast
Snack Options	No
Ventilation/Light System	
Charcoal Filter	Yes - 1
Cooktop Light	Yes - High / Night / Off
Duct/Ductless Vent	Yes
Exhaust Duct	Convertible (Ventilation is convertible to be either ducted outside or recirculated inside requiring no ducting.)
Exhaust Fan Speeds	Yes - High / Low / Off
Grease Filter	Yes - 2
Vent Style	Hidden
Auto Features	
Beverage	No
Microwave Oven Specifications	
Interior Light	LED
Interior Light Wattage	1.2
Turntable Diameter	13-5/8"
Cooking Controls	
Interface	Glass Touch
Vent & Light System	
Work-Area Light	LED

FRIGIDAIRE GALLERY.

FGBM15WCVF

Available Colors : Stainless Steel

Over-The-Range Microwave

1.5 Cu. Ft. Over-The-Range Microwave with Convection

Version: 10/19

Installation Drawing

Locate 120V/60Hz grounded outlet inside upper cabinet Microwave MUST Bottom edge of cabinet MUST be be mounted to BOTH a top cabinet[†] AND a wall* 30" min. from cooking surface 30" 13" Cabinet MUST Rear Wall 161/2" be capable of min. max* supporting a total 30" min. load of 135 lbs. 66" min. from floor (or 150 lbs.**) 2" min. to top of Backsplash microwave Power cord Blower plate allows for vertical location or horizontal ducting 16 3/8 " rear †When installing beneath smooth, flat cabinets, refer to cabinet extrusion template for detailed power cord clearance instructions *Can NOT be installed in island or peninsula cabinet arrangements lower 297/8" extrusion **If cabinet depth (including doors) is deeper than 13", unit MUST 153/4" be spaced out from rear wall using adequate materials (supporting Allow at least 26" clearance 150 lbs.) to allow proper top vent air exhaust/intake

for door depth when open