



DRYWALL PRIMER & SEALER

NO. L2042



PRODUCT INFORMATION

KILZ® DRYWALL PRIMER & SEALER is formulated to prime and seal new, uncoated drywall which helps achieve a uniform, professional quality finish.

RECOMMENDED USES:

Recommended use on:

- New Drywall/Gypsum Board

PRODUCT SPECIFICATIONS:

Fill / Max Tint Load:

- No. L204211 128 oz. / 2 oz.
- No. L204202 2-GALLON 256 oz. / 4 oz.
- No. L204205 5-GALLON 640 oz. / 10 oz.

Resin Type: Polyvinyl Acetate

Weight per Gallon: 9.77 lbs.

% Solids by Volume: 16%

% Solids by Weight: 27%

VOC: <100 g/L

Flash Point: N/A

Viscosity: 95 – 105 KU

Recommended Film Thickness:

- Wet: 5.3 mils / Dry: 0.8 mils @ 300 Sq. Ft./Gal.
- Wet: 4.0 mils / Dry: 0.6 mils @ 400 Sq. Ft./Gal.

Coverage: 300 – 400 Sq. Ft./Gal. depending on the surface texture, porosity and application method. Does not include the loss of material from spraying.

APPLICATION:

Brush: Nylon / Polyester Blend

Roller: 3/8" – 1/2" nap

Airless Spray: Fluid pressure of 2,500 – 3,200 psi

Tip: .017" – .021"

Filter: 60 mesh

Dry Time: @ 77°F, 50% RH

Longer dry time required in cooler temperatures and in higher humidity.

To Touch: 30 minutes

To Recoat: 1 hour

SURFACE PREPARATION:

Cover all nail and screw heads with joint compound according to directions and sand to smooth surface.

Tape drywall and apply joint compound and allow to fully cure according to directions prior to priming.

Sand to smooth surface before priming.

Wipe off dust with a damp cloth, allow to dry thoroughly.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC.** Contact the National Lead Information Center at 1-800-424-LEAD or visit www.epa.gov/lead.

CLEAN UP:

Use soap and water to clean hands, tools and spills. For recycling or disposal of empty containers and unused product, contact your household refuse collection service.

CAUTIONS/LIMITATIONS:

IMPORTANT! Do not open can without reading instructions.

- Interior use only.
- For use on uncoated drywall only.
- Do not use on floors.
- Do not use when air and surface temperatures are below 50°F or above 90°F.
- Allow 2 weeks for full cure before washing or cleaning.
- Do not use over glossy surfaces.
- Do not topcoat with glossy paint finishes.
- Shelf life under normal conditions is two years unopened.

USE ONLY WITH ADEQUATE VENTILATION

CAUTION: KEEP OUT OF REACH OF CHILDREN

DO NOT TAKE INTERNALLY

WARNING
Cancer and Reproductive Harm— www.P65Warnings.ca.gov

COMPLIES WITH THE BELOW AS OF 11/1/2020

SCAQMD	YES	LADCO	YES
CARB	YES	AIM	YES
OTC	YES	LEED v.3 (2009) [†]	YES

[†]Please visit www.usgbc.org/LEED for additional details.

WARNING! CAUSES EYE AND SKIN IRRITATION.

MAY CAUSE RESPIRATORY TRACT IRRITATION. CONTAINS CALCIUM CARBONATE, CRYSTALLINE SILICA AND TITANIUM DIOXIDE. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING VAPORS, SPRAY MIST AND SANDING DUST. Sanding, grinding or abrading may release sanding dust, which may be harmful if inhaled and has been shown to cause lung damage or cancer with long term exposure. Do not breathe dusts, vapor, or spray mist. To avoid breathing in dust, vapors, and spray mist, open windows and doors or use other means to ensure fresh air entry during application, drying, sanding, and/or abrading. If properly used, a respirator (NIOSH approved with particulate pre-filter) may offer additional protection and should be used if adequate ventilation cannot be provided; obtain professional advice before using. If you experience eye watering, headaches, or dizziness during application or drying, increase fresh air or leave the area. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use.

FIRST AID: If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 20 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

CAUTION: KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY



DRYWALL PRIMER & SEALER

NO. L2042



GENERAL INFORMATION:

LIFETIME LIMITED WARRANTY: Masterchem Industries LLC warrants to you, the original residential consumer purchaser, the performance of this product as described on this label for so long as you reside in your home. If this product is found to be defective upon inspection by its representative, Masterchem Industries LLC will, at its option and upon presentation of proof-of-purchase (the original receipt), either furnish an equivalent amount of new product or refund the original purchase price of this product to you. This warranty is not transferable. This warranty excludes (1) labor and costs of labor for the application or removal of any product, and (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. To the extent permitted by applicable law, any implied warranties including the implied warranties of merchantability and of fitness for a particular purpose, are limited to the duration of this express warranty. Some states do not allow limitations on how long an implied warranty lasts, so the above limitation may not apply to you. This warranty gives you specific legal rights and you may also have other rights, which vary from state to state. Note to residents of the State of New Jersey: The provisions of this warranty, including its limitations, are intended to apply to the fullest extent permitted by the laws of the State of New Jersey. For warranty service, call: 1-866-774-6371, or email: techservice@masterchem.com. Masterchem Industries LLC reserves the right to inspect any and all application of the product prior to processing your claim made under this warranty.