

LED Canopy & Parking Garage Light, 25W



🕦 🕲 **FC C E**



Features

70% less power consumption compared to

- HID lamps
- \blacklozenge 50,000 life hours vs. 10,000 to 15,000 for HID lamps
- Powerful lumen output combined with effective light distribution
- No mercury or other harmful elements
- Adjustable CCT 3000K, 4000K, or 5000K

Applications Gas stations

- Commercial awnings
- Entry ways
- Covered walkways
- Loading areas
- Parking garage lighting
- Other general lighting

Product Description

The SunRiver G2 LED Canopy light offers significant energy savings, superior performance, reduced maintenance and unsurpassed durability in a fixture that is designed with a modern aesthetic and more streamlined profile than seen in traditional canopy lighting fixtures. SunRiver canopy lights deliver enhanced lighting control and dramatically improved lighting values, resulting in better uniformity and overall visibility. Bi-level Motion sensor option available. Housing available in brown or white (pictured).

Technical Data

Product No.	Watt	Size(inch)	ССТ	Luminous Output	Voltage
LTRSC25W	25	ф10*3.1	3000K-5000K	~3250lm	AC120~277V
Luminous Intensity Distribution Curve Illuminance at a Distance					
140 130 120 110		140 130 120 110	1.0	141.60 12.50/12.52 148.3 8.96	
100 90 80	189	100 90 80	3.0	35.40 25.01/25.05 593.3 2.24	
70 60 50 40	379 758	50	6.0 7.0 8.0	11.56 43.76/43.83 1817.0 0.73	
Avera	30 20 10 0 1 ge Diffuse Angle(C180 - C90-		Dh Dy Beam Angle(B)		

3479 NW Yeon Avenue, Portland, OR 97210 WWW.LEDTRAIL.COM SALES@LEDTRAIL.COM PHONE: 971-200-2760 FAX: 800-507-8044

©2020-2021 LED Trail. The products and any diagrams, and images in this catalog are proprietary to LED Trail. No reproduction of images or content is allowed. LED Trail reserves the right to discontinue or change the design, components or technical specifications of its products at any time and without prior notice. Pictures shown may vary from actual products. Some certifications may not apply to all products.