

## SAFETY DATA SHEET

## 1. Identification

Product identifier NatureWood-CA Treated Wood

Other means of identification

SDS number 294-KPC

**Recommended use** Preservative Treated Wood for various interior and exterior applications.

**Recommended restrictions** None known.

Manufacturer/Importer/Supplier/Distributor information

Company Name

Koppers Performance Chemicals Inc.

Address

1016 Everee Inn Rd., Griffin, GA 30224

**Telephone number** 770-233-4200

Contact personRegulatory Manager, KPC Inc.Emergency TelephoneCHEMTREC 1-800-424-9300

Number

E-mail KPCmgrsds@koppers.com

2. Hazard(s) identification

Physical hazards Not classified.

Health hazardsSensitization, skinCategory 1

Carcinogenicity (inhalation) Category 1A

OSHA defined hazards Combustible dust

Label elements



Signal word Danger

**Hazard statement** May cause cancer by inhalation. May cause an allergic skin reaction. May form combustible dust

concentrations in air.

**Precautionary statement** 

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Prevent dust accumulation to minimize explosion hazard. Ground/bond container and receiving

dust accumulation to minimize explosion hazard. Ground/bond container and receiving equipment. Wear protective gloves/protective clothing/eye protection/face protection.

Contaminated work clothing must not be allowed out of the workplace. Wash thoroughly after

handling. Observe good industrial hygiene practices.

**Response** If exposed or concerned: Get medical advice/attention. If on skin: Wash with plenty of water/. If

skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and

wash before reuse. In case of fire: Use CO2, foam or water spray for extinction.

**Storage** Store away from incompatible materials.

**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

## 3. Composition/information on ingredients

## **Mixtures**

Chemical name	CAS number	%
Wood/Wood Dust	N/A	>90

Copper Carbonate (expressed as elemental copper)	12069-69-1	<1
Tebuconazole	107534-96-3	<1
Propiconazole	60207-90-1	<1

#### **Composition comments**

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Depending on the additives applied to the treating solution, this wood may also contain <1 % of mold inhibitors, <1% of a non-hazardous wax emulsion, and <% of a colorant.

## 4. First-aid measures

#### Inhalation

Move to fresh air. If breathing is difficult, give oxygen. Get medical attention immediately. Some species may cause allergic respiratory reactions with asthma-like symptoms in sensitized individuals.

#### Skin contact

Remove contaminated clothing. Wash skin thoroughly with soap and water for several minutes. Prolonged contact with treated wood and/or treated wood dust, especially when freshly treated at the plant, may cause irritation to the skin. Abrasive handling or rubbing of the treated wood may increase skin irritation. Some wood species, regardless of treatment, may cause dermatitis or allergic skin reactions in sensitized individuals. If wood splinters are injected under the skin, get medical attention. In case of rashes, wounds or other skin disorders: Seek medical attention and bring along these instructions.

## Eye contact

Do not rub eye. Immediately flush eye(s) with plenty of water. Remove any contact lenses and open eyelids wide apart. If irritation persists get medical attention.

### Ingestion

Rinse mouth thoroughly if dust is ingested. Get medical attention if any discomfort continues.

Most important symptoms/effects, acute and delayed

May cause allergic skin disorders in sensitive individuals. Wood dust: May cause nasal dryness, irritation and mucostasis. Coughing, wheezing, sneezing, sinusitis and prolonged colds have also been reported. Depending on wood species may cause respiratory sensitization and/or irritation. Symptoms can include irritation, redness, scratching of the cornea, and tearing. May cause eczema-like skin disorders (dermatitis). Airborne treated or untreated wood dust may cause nose, throat, or lung irritation and other respiratory effects.

# Indication of immediate medical attention and special treatment needed

Treat symptomatically. Respiratory ailments and pre-existing skin conditions may be aggravated by exposure to wood dust.

## General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

## 5. Fire-fighting measures

## Suitable extinguishing media

Unsuitable extinguishing media

Carbon dioxide, regular foam, dry chemical, water spray, or water fog.

Do not use water jet as an extinguisher, as this will spread the fire.

## Specific hazards arising from the chemical

Depending on moisture content, and more importantly, particle diameter and airborne concentration, wood dust in a contained area may explode in the presence of an ignition source. Wood dust may similarly deflagrate (combustion without detonation like an explosion) if ignited in an open or loosely contained area. An airborne concentration of 40 grams (40,000 mg) of dust per cubic meter of air is often used as the LEL for wood dusts. Reference NFPA Standards-654 and 664 for guidance.

# Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire. Selection of respiratory protection for firefighting: follow the general fire precautions indicated in the workplace.

# Fire fighting equipment/instructions

Use water spray to cool fire exposed surfaces and to protect personnel.

**General fire hazards** May form combustible dust concentrations in air.

## 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Avoid generation and spreading of dust. Avoid spread of dust. Avoid inhalation of dust. Provide adequate ventilation. Wear appropriate personal protective equipment (See Section 8).

Methods and materials for containment and cleaning up

Sweep or vacuum up spillage and collect in suitable container for disposal. If not possible, gently moisten dust before it is collected with shovel, broom or the like. Containers must be labeled. For waste disposal, see Section 13 of the SDS.

### **Environmental precautions**

For good industrial practice avoid release to the environment.

## 7. Handling and storage

Precautions for safe handling

Avoid prolonged or repeated breathing of dust. Avoid prolonged or repeated contact with skin. Wear appropriate personal protective equipment. Do not smoke. Change contaminated clothing. Persons susceptible for allergic reactions should not handle this product. Do not burn preserved wood. Do not use preserved wood as Mulch. Routine housekeeping should be instituted to ensure that dusts do not accumulate on surfaces.

Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks and open flame. Store in tightly closed original container in a dry, cool and well-ventilated place. Store away from incompatible materials (See Section 10).

## 8. Exposure controls/personal protection

#### Occupational exposure limits

U.S. - OSHA

Components	Туре	Value	Form
Wood Dust (CAS N/A)	PEL	5 mg/m3	Respirable dust.
		15 mg/m3	Total fraction.
ACGIH			
Components	Туре	Value	Form
Wood Dust (CAS N/A)	TWA	1 mg/m3	Inhalable fraction.
US. NIOSH: Pocket Guide to Cher	nical Hazards		
Components	Туре	Value	Form
Copper Carbonate (expressed as elemental	TWA	1 mg/m3	Dust and mist.
copper) (CAS 12069-69-1)			
Wood Dust (CAS N/A)	TWA	1 mg/m3	Dust.

**Biological limit values** 

Appropriate engineering

controls

No biological exposure limits noted for the ingredient(s).

Provide sufficient general/local exhaust ventilation to maintain inhalation exposures below current exposure limits and areas below explosive dust concentrations. Shower, hand and eye washing facilities near the workplace are recommended.

## Individual protection measures, such as personal protective equipment

Eye/face protection

Wear safety glasses with side shields when handling, cutting, sanding or grinding this material. Use a face shield during processes that may generate excessive dusts and splinters.

Skin protection

Other

Hand protection

Wear chemical resistant (rubber, neoprene or nitrile) gloves when handling freshly treated wood at

the treating plant. Otherwise, wear puncture resistant work gloves, such as leather.

Respiratory protection

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Use a NIOSH–approved respirator if there is a potential for exposure to dust exceeding exposure limits (See 29 CRF 1910.134, respiratory protection standard).

Wear long sleeve shirt, long pants and gloves when working with freshly treated wet wood.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

If wood dust contacts the skin, workers should wash the affected areas with soap and water. Clothing contaminated with wood dust should be removed, and provisions should be made for the safe removal of the chemical from the clothing. Persons laundering the clothes should be informed of the hazardous properties of wood dust. A worker who handles wood dust should thoroughly wash hands, forearms, and face with soap and water before eating, using tobacco products, using toilet facilities, applying cosmetics, or taking medication. Workers should not eat, drink, use tobacco products, apply cosmetics, or take medication in areas where wood dust is handled, or processed. Observe any medical surveillance requirements.

## 9. Physical and chemical properties

**Appearance** 

Physical state Solid.

Form Solid Wood. Dust.
Color Not available.
Odor No odor.

Odor threshold Not applicable.

PH Not applicable.

Melting point/freezing point Not applicable.

Initial boiling point and boiling Not applicable.

range

Flash point Not available.

Evaporation rate Not applicable.

Flammability (solid, gas) Combustible dust.

Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

(%)

Flammability limit - upper

Not available.

(%)

Explosive limit - lower (%) Not available.
Explosive limit - upper (%) Not available.

Vapor pressure Not applicable.

Vapor density Not available.

Relative density Not available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not applicable.

(n-octanol/water)

Auto-ignition temperatureNot available.Decomposition temperatureNot available.ViscosityNot applicable.

## 10. Stability and reactivity

**Reactivity**The product is non-reactive under normal conditions of use, storage and transport.

**Chemical stability** Stable at normal conditions.

Possibility of hazardous

reactions

Hazardous reactions do not occur.

Conditions to avoid Avoid heat, sparks, open flames and other ignition sources. Minimize dust generation and

accumulation. Avoid contact with incompatible materials.

**Incompatible materials** Strong oxidizing agents. Reducing agents.

Hazardous decomposition

products

Combustion products may yield irritating and toxic vapors/fumes of organic materials, and oxides

of carbon and nitrogen.

## 11. Toxicological information

Information on likely routes of exposure

**Inhalation** Wood dust, treated or untreated, is irritating to the nose, throat and lungs. Prolonged or repeated

inhalation of wood dusts may cause respiratory irritation, recurrent bronchitis and prolonged colds. Some species may cause allergic respiratory reactions with asthma-like symptoms in sensitized individuals. Prolonged exposure to wood dusts by inhalation has been reported to be associated

with nasal and paranasal cancer.

Skin contact Handling may cause splinters. Prolonged contact with treated wood and/or treated wood dust,

especially when freshly treated at the plant, may cause irritation to the skin. Abrasive handling or rubbing of the treated wood may increase skin irritation. Some wood species, regardless of

treatment, may cause dermatitis or allergic skin reactions in sensitized individuals.

**Eye contact** Dust may irritate the eyes.

**Ingestion** Not likely, due to the form of the product. However, ingestion of dusts generated during working

operations may cause nausea and vomiting. Certain species of wood and their dusts may contain

natural toxins, which can have adverse effects in humans.

Symptoms related to the physical, chemical and toxicological characteristics

May cause allergic skin disorders in sensitive individuals. Wood dust: May cause nasal dryness, irritation and mucostasis. Coughing, wheezing, sneezing, sinusitis and prolonged colds have also been reported. Depending on wood species may cause respiratory sensitization and/or irritation. Symptoms can include irritation, redness, scratching of the cornea, and tearing. May cause eczema-like skin disorders (dermatitis). Airborne treated or untreated wood dust may cause nose, throat, or lung irritation and other respiratory effects.

Information on toxicological effects

**Acute toxicity** Not expected to be acutely toxic.

Components Species **Test Results** Propiconazole (CAS 60207-90-1) Acute Oral LD50 Rat 1517 mg/kg Tebuconazole (CAS 107534-96-3) Acute Dermal LD50 Rat > 5000 mg/kg Inhalation LC50 Rat > 2.07 mg/lOral LD50 Rat 1750 mg/kg Skin corrosion/irritation Dust may irritate skin.

Serious eye damage/eye

Dust may irritate the eyes.

Respiratory or skin sensitization

**ACGIH Sensitization** 

Wood Dust (CAS N/A)

Dermal sensitization

Respiratory sensitization

Respiratory sensitization

Exposure to wood dusts can result in hypersensitivity,

Skin sensitization

May cause an allergic skin reaction. Exposure to wood dust can result in the development of contact dermatitis. The primary irritant dermatitis resulting from skin contact with wood dusts consist of erythema, blistering, and sometimes erosion and secondary infections occur.

Germ cell mutagenicity

No component of this product present at levels greater than or equal to 0.1% is identified as a mutagen by OSHA.

mutagen by OSHA.

Carcinogenicity

May cause cancer by inhalation.

This classification is based on an increased incidence of nasal and paranasal cancers in people

exposed to wood dusts.

IARC Monographs. Overall Evaluation of Carcinogenicity

Wood Dust (CAS N/A) 1 Carcinogenic to humans.

NTP Report on Carcinogens

Wood Dust (CAS N/A)

Known To Be Human Carcinogen.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

**Reproductive toxicity**This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

**Aspiration hazard** Not likely, due to the form of the product.

Chronic effects Chronic exposure to wood dusts can result in pneumonitis, and coughing, wheezing, fever and the

other signs and symptoms associated with chronic bronchitis.

**Further information** Tebuconazole and propiconazole, components of NatureWood-CA Treated Wood, have been

classified by EPA as possible human carcinogens.

Acute toxicity testing has not been performed on the treated wood.

NatureWood-CA Treated Wood SDS US

5/8

## 12. Ecological information

**Ecotoxicity** The product is not classified as environmentally hazardous. This product is not expected to leach

harmful amounts of preservative into the environment.

Components Species Test Results

Copper Carbonate (expressed as elemental copper) (CAS 12069-69-1)

EC50 Balanus balanoides 350 - 480 μg/l, 48 hours

**Persistence and degradability** No data is available on the degradability of this product.

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient n-octanol / water (log Kow)

Propiconazole (CAS 60207-90-1) 3.5

**Mobility in soil** The product is insoluble in water.

Mobility in general The product is not volatile but may be spread by dust-raising handling.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

## 13. Disposal considerations

**Disposal instructions**Dispose in accordance with applicable federal, state, and local regulations. Do not discharge into

drains, water courses or onto the ground.

**Local disposal regulations** Dispose of in accordance with local regulations.

Hazardous waste code The Waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose in accordance with all applicable regulations. Do not discharge into drains, water courses

or onto the ground.

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

## 14. Transport information

DOT

Not regulated as dangerous goods.

**IATA** 

Not regulated as dangerous goods.

**IMDG** 

Not regulated as dangerous goods.

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78 and

the IBC Code

## 15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

**CERCLA Hazardous Substance List (40 CFR 302.4)** 

Copper Carbonate (expressed as elemental copper) LISTED

(CAS 12069-69-1)

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous Yes

chemical

NatureWood-CA Treated Wood SDS US

6/8

#### SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.	
Copper Carbonate (expressed as elemental copper)	12069-69-1	<1	
Propiconazole	60207-90-1	<1	

## Other federal regulations

## Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

## Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

## **US state regulations**

#### **US. Massachusetts RTK - Substance List**

Not regulated.

#### US. New Jersey Worker and Community Right-to-Know Act

Copper Carbonate (expressed as elemental copper) (CAS 12069-69-1)

Propiconazole (CAS 60207-90-1)

Wood Dust (CAS N/A)

## US. Pennsylvania Worker and Community Right-to-Know Law

Wood Dust (CAS N/A)

#### **US. Rhode Island RTK**

Copper Carbonate (expressed as elemental copper) (CAS 12069-69-1)

Propiconazole (CAS 60207-90-1)

#### **US. California Proposition 65**

WARNING: This product contains a chemical known to the State of California to cause cancer.

#### US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance

Wood Dust (CAS N/A)

#### **International Inventories**

Country(s) or region Inventory name On inventory (yes/no)\*
United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes

\*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other information, including date of preparation or last revision

Issue date21-April-2015Revision date01-June-2015

Version # 02

Further information HMIS® is a registered trade and service mark of the NPCA.

PERCENTAGE OF ACTIVE INGREDIENTS PER RETENTION LEVEL %:

0.06 pcf

Copper Carbonate expressed as Elemental Copper 0.04-0.06%, Tebuconazole 0.001-0.002%,

Propiconazole 0.001-0.002%

0.15 pcf

Carbonate expressed as Elemental Copper 0.10-0.20%, Tebuconazole 0.002-0.004%,

Propiconazole 0.002-0.004%

0.31 pcf

Copper Carbonate expressed as Elemental Copper 0.20-0.40%, Tebuconazole 0.004-0.007%,

Propiconazole 0.004-0.007%

E - Safety Glasses, Gloves, Dust Respirator

HMIS® ratings Health: 1\*

Flammability: 1 Physical hazard: 0 Personal protection: E

NatureWood-CA Treated Wood SDS US

7/8

## **NFPA** ratings



## **Disclaimer**

Koppers Performance Chemicals Inc. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.