



### **Inspection:**

- Always inspect your tiles before they are installed, as **installation of material constitutes acceptance**.
- Any questions as to acceptability must be resolved before installation. Apollo Tile is in no way responsible for the installation of our tiles or thereafter. The responsibility for correct installation rests with the end user.
- The responsibility for correct installation rests with the end user. Some may be susceptible to scratching in handling, installation and use. Expect a slight color variation from production run to production run

### **Installation:**

- To prolong the life and beauty of your installation, it is best to secure a licensed installer familiar with the industry standards established in the NTCA, ASTM, M.I.A. and ANSI handbooks for tile and trade installation.
- Porcelain tiles, while durable, are not completely stain- or damage-proof and require proper care. Different finishes hold contaminants differently; glossy tiles resist stains better but show scratches more easily. Maintenance frequency depends on the tile's location and usage, with busy areas requiring more upkeep.
- While not mandatory, sealing helps protect grout and prolongs tile life. Please refer to sealers Manufacturer instructions prior to sealing. Test in a small area before sealing entire surface to ensure suitability. Contact your purchase location for additional information on these types of sealers.
- We recommend installing porcelain over a clean, sound, and flat concrete or mortar substrate. The surface should be free of contaminants or any condition that could compromise the bond of the tile. Always layout your material prior to installation to ensure the appearance meets desired results.
- Use a high quality, well maintained wet saw with a diamond blade designed for cutting materials. Using a poorly maintained tile saw or a blade will cause the tile to chip during cutting. Always cut tile very slowly to avoid chipping.
- Grout joints should be packed full and free of all voids and pits. Excess grout should be cleaned from the surface as the work progresses, while grout is fresh and before it hardens. Prior to grouting, test in a small area to make sure that the right color grout is chosen and that the surface does not scratch during grouting.

### **Care and Maintenance:**

Porcelain tiles, while durable, require regular maintenance due to their porous nature. To maximize the life of your mosaic and retain its artistic integrity, please consider the following:

- Use only a mild, pH-neutral detergent cleaner and damp sponge or rag to clean your mosaic.
- **Do not** use acid, alkaline, and solvent-based cleaners. They can damage and/or discolor the tiles and the grout.
- **Do not** allow soap, bleach or other cleaning solutions set on the surface.
- **Do not** wax any part of your mosaic.
- **Do not** let stains sit on your mosaic's surface for extended periods. Clean promptly.