

Porto II™ is inspired by the simplistic look of concrete and stone in large format sizes and a range of colors. Available in matte or polished, Porto II is ideal for both residential and commercial spaces.

PORTO II™

Glazed Porcelain



FLOOR / WALL

RESIDENTIAL

COMMERCIAL

INDOOR

OUTDOOR

POOL



White



Ivory



Fawn



Charcoal

Mosaics



White



Ivory



Fawn



Charcoal

SIZES	<div><div></div><div></div><div></div><div></div><div></div></div>							
	32" x 32" 31.50" x 31.50"	24" x 24" 23.62" x 23.62"	12" x 24" 11.81" x 23.62"	12" x 12" Mesh	3" x 12" Floor SBN			
THICKNESS	10mm	8.8mm	8.8mm	9mm	9mm			
FACES	8	8	10	N/A	N/A			
FINISH	Matte & Polished	Matte & Polished	Matte & Polished	Matte	Matte & Polished			
EDGE	Rectified	Rectified	Rectified	Cut	Cut/Rounded			
Grout Joint Recommendation	3/16"	3/16"	3/16"	3/16"	3/16"			
TESTING	Abrasion Resistance C1027	Breaking Strength C648	Chemical Resistance C650	Water Absorption C373	DCOF ANSI A137.1	Scratch Hardness MOHS	Shade Variation Rating	
	III	>550 lbf	Resistant	<0.50%	>0.42 (Matte) <0.42 (Polished)	7 (Matte) 6 (Polished)	V3	

Polished not recommended for use as commercial or outdoor flooring.

Product and Installation Details | ANSI A108.02 Section 4.3.8.2 - For running bond/brick joint patterns utilizing tiles (square or rectangular) where the side being offset is greater than 18" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the tile manufacturer. If an offset greater than 33% is specified, specifier and owner must approve mock-up and lippage.



- Sustainability Attributes

 - Red List Free
 - Health Product Declaration (HPD) provided upon request
 - Product Packaging is 100% recyclable

- VOC Free

*For more information visit www.emser.com. Always consult a professional for proper usage and installation.