


Features	
Controls	Ready-Select™
Surface Type	Ceramic Glass
Right Front Element (Watts)	9" - 2,500
Right Rear Element (Watts)	6" - 1,200
Left Front Element (Watts)	6" - 1,200
Left Rear Element (Watts)	9" - 2,500
Hot-Surface Indicator Light	Yes
Control Location	Right Side
Knob Color	Color-Coordinated
Knob Type	Plastic
Specifications	
Power Supply Connection Location	Right Rear
Voltage Rating	240V/208V/60Hz
Connected Load (kW Rating) @ 240/208 Volts¹	TBD
Amps @ 240/208 Volts	TBD
Minimum Circuit Required (Amps)	30
Approved for Electric Single Wall Oven Combination Installation²	Yes
Shipping Weight (Approx.)	45 Lbs.

¹Single phase 3- or 4-wire cable, 120/240 or 120/208 Volt, 60 Hertz AC only electrical supply with ground required on separate circuit fused on both sides of line.
²Cooktops are approved for installation above any of our Electric Single Wall Ovens.



NOTE: Always consult local and national electric codes. Refer to Product Installation Guide for detailed installation instructions on the web at frigidaire.com.



Product Dimensions	
A - Height	2-5/8"
B - Width	30-3/4"
C - Depth	21-1/2"

Cutout Dimensions	
Height	5"
Width (Min.)	29-5/8"
Width (Max.)	29-3/4"
Depth (Min.)	20-1/4"
Depth (Max.)	20-1/2"

Granite Countertop Installation Kit available.