

## SPECIFICATIONS

### DESCRIPTION

- Pulldown system offers smooth operation, easy movement and secure docking
- Metal construction with various finishes identified by suffix
- Quick connect installation - Duralock™
- PowerBoost™ spray technology
- Pulldown spray with 68" braided hose
- Flexible supply lines with 3/8" compression fittings
- High arc spout provides height and reach to fill or clean large pots while pulldown wand provides the maneuverability for cleaning or rinsing
- Faucet designed for handle to be mounted on right side

### OPERATION

- Lever-style handle
- Temperature controlled by 100° arc of handle travel
- Operates with less than 5 lbs. of force
- Operates in stream or spray mode in the pullout or retracted position


### FLOW

- Flow is limited to 1.5 gpm (5.7 L/min) max at 60 psi

### CARTRIDGE


- 1255™ Duralast™ cartridge for single handle faucets

### STANDARDS

- Third party certified to IAPMO Green, ASME A112.18.1/CSA B125.1 and all applicable requirements therein including NSF 61/9 & 372
- Meets CalGreen and Georgia SB370 requirements
- Complies with California Proposition 65 and with the Federal Safe Drinking Water Act
- The backflow protection system in the device consists of two independently operating check valves, a primary and a secondary which prevent backflow
- ADA  for lever handle

### WARRANTY


- Lifetime limited warranty against leaks, drips, and finish defects to the original homeowner Visit [www.moen.com/support](http://www.moen.com/support) for complete details and limitations



### Joric Single Handle Pre-Rinse Spring Pulldown Kitchen Faucet

**MODEL:** 87580 Series

**NOTE:** This faucet is designed to be installed through 1 hole, 1-1/2" (38mm) min. Dia. 1, 2, 3, Or 4 Hole installation (deckplat and soap included)



**CRITICAL DIMENSIONS** DO NOT SCALE