

INSTALLATION AND SAFETY INSTRUCTIONS

FOR YOUR SAFETY

WARNING: BE SURE THE ELECTRICITY TO THE WIRES YOU ARE WORKING ON IS SHUT OFF; EITHER THE FUSE IS REMOVED OR THE CIRCUIT BREAKER IS SHUT OFF.

GENERAL

You don't need special tools to install this fixture.

Be sure to follow the steps in the order given. Under no circumstances should a fixture be hung on house electrical wires, nor should a swag type fixture be installed on a ceiling, which contains a radiant type heating system. Read instructions carefully. If you are unclear as to how to proceed, consult a qualified electrician.

NOTE: Proper wiring is essential for the safe operation of this fixture.

FIXTURE ASSEMBLY

Carefully removed the fixture from the carton and check that all parts are included as shown in figure. Be careful not to misplace any of the screws or parts, which are needed to install this fixture.

INSTALLATION

Step 1: Install stem (K) to the hexagon coupling (L).

Step 2: Adjust the length to your desired hanging length with connecting the canopy (G), a 18" stem (K), a 12" stem (J) and a 6" stem (I). Secure the canopy (G) and the stems tightly.

Step 3: Install the bulbs (not included). Check relamping label at socket area or packaging for maximum allowed wattage.

Step 4: Put the glass shade (N) onto the lamp base (L), secure them with the screws (M) tightly.

Step 5: Secure the mounting bracket (C) to the outlet box (not included) tightly by using screw (F).

Step 6: Pull out the source wires from the outlet box (not included).

Make wire connections with wire connectors (B) as follows:

--Using wire connectors (B), connect the RIBBED fixture wire (with no words on it) to the white (neutral) supply wire from the outlet box (not included).

--Using wire connectors (B), connect the SMOOTH fixture wire (with words on it) to the black (live) supply wire from the outlet box (not included).

--Connect the ground wire from the outlet box (not included) and the ground wire from the fixture to the ground screw. Tighten the ground screw to secure ground wires to the mounting bracket (C).

Carefully put the wires back into the outlet box (not included).

Step 7: Put the fixture onto the mounting bracket (C), secure it by using nuts (H).

Step 8: Turn on the power.

CLEANING

To clean, wipe fixture with a soft and dry cloth. Do not use abrasive materials such as scouring pads or powders, steel wool or abrasive paper.

Line art shown may not exactly match the fixture enclosed. However, the installations do apply to this fixture.

ITEM NO: 9201-MG/MB

