



Rating label for Fanaway fan:(date code format: PO#+WWYY)

 SKU#: 51105001 Model No: BI-48" FAN-CAORB-USA-FA 120Vac, 60Hz, Max.135W, Max.1.2A, Fan: 60W Light: Max. 3 x 25 W, E26 Date Code: XXXXXXXX-XXXX Made in China		CONFORMS TO UL STD 507 CERTIFIED TO CSA STD. C22.2 NO.113
---	--	---

 SKU#: 51105101 Model No: BI-48" FAN-CAGS-USA-FA 120Vac, 60Hz, Max.135W, Max.1.2A, Fan: 60W Light: Max. 3 x 25 W, E26 Date Code: XXXXXXXX-XXXX Made in China		CONFORMS TO UL STD 507 CERTIFIED TO CSA STD. C22.2 NO.113
--	---	---

Rating label for each Lamp holder :

CAUTION – RISK OF FIRE, MAX. 25W E26

PRECAUCIÓN - RIESGO DE INCENDIO, E26 25W MÁX.

Other label on the fan

Mounting bracket:

WARNING-To Reduce The Risk Of Fire, Electric Shock, Or Personal Injury, Mount To Outlet Box Marked Acceptable For Fan Support of 15.9kg(35lbs) or less And Use Mounting Screws Provided With The Outlet Box and/or Support Directly From Building Structure

ADVERTENCIA-Para reducir el riesgo de incendio, descarga eléctrica o lesión, móntelo a una caja eléctrica clasificada como Apropiaada para sostener ventiladores de 15,9kg(35lb) o menos, y utilice los tornillos de montaje suministrados con la caja eléctrica y/o fíjelo directamente a la estructura del edificio.

COUPLING

CAUTION: Set crews must be tightened securely before fan is operated.
PRECAUCIÓN: Los tornillos de ajuste deben estar bien apretados antes de encender el ventilador.

DECORATIVE HOUSING

CAUTION:To Reduce The Risk Of Injury To Persons, Install Fan So That The Blade Is At Least 2.1 Meters (7 Feet) Above The Floor.
PRECAUCIÓN: Para reducir el riesgo de lesión, instale el ventilador de tal manera que las aspas estén a 2,1 m (7 pies) como mínimo por encima del suelo.