

Warning! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1.800.424.LEAD or log on to www.epa.gov/lead.

This product is certified by Coating Research Group Inc. to meet performance and environmental standards as shown on www.greenwisepaint.com. The addition of VOC-containing colorants may increase the final VOC of a tinted paint.

CAS#	Chemical Ingredients
7732-18-5	Water
37244-96-5	Nepheline Syenite
25265-77-4	Ester Alcohol
1309-37-1	Iron Oxide
Not Available+	Alkyd / Acrylic Resin Solids
(+)Contents partially unknown	

MAXIMUM VOC CONTENT: 100 g/L
*Based upon ASTM D6886 testing. Product meets or exceeds current OTC VOC standards (www.otc.air.org). VOC testing performed on product formulation prior to application. The product may produce emissions and odors during application, curing and for some time afterwards. Depending upon color choice, non zero VOC colorant added to this product may significantly increase VOC levels.



TRANSPARENT STAIN + SEALER



EASY TO APPLY



RESISTS CRACKING,
PEELING, BLISTERING
AND MOISTURE



SOAP & WATER CLEANUP



Lightly tones
the wood,
enhancing it
when a more
natural
appearance
is desired

22546 Teak

128 FL OZ
3.79 L

Dual Dispersion Transparent Stain + Sealer boasts State of the Dual Dispersion one-coat technology to provide the best features of traditional oil-based paints and latex paints. As a finish it has the excellent flow, leveling and durability of oil-based paint with the fast-dry time and soap and water clean-up of latex paint. Dual Dispersion Transparent Stain + Sealer Finish resists cracking, peeling blistering and moisture. This product can be used on multiple wood surfaces including dense hardwoods such as mahogany, teak and fir.

RECOMMENDED USE: Unfinished/Bare Wood: Deck Boards, Railings, Posts, Clapboards, Shingles, Shakes, Fencing, Outdoor Furniture **FOR WOOD SUBSTRATES ONLY.**

CAUTION! KEEP OUT OF REACH OF CHILDREN. DO NOT TAKE INTERNALLY. Close container after each use.

Avoid contact with skin.

FIRST AID: If swallowed, do not induce vomiting. Call a physician immediately.

DISPOSAL: Dispose of contents in accordance with applicable local/national/regional/international regulations.

SEE SAFETY DATA SHEET.

GENERAL SURFACE PREPARATION: All wood must be thoroughly cleaned of Mold, Mildew, Dirt, Grease, Grime, Mill Glaze, Previous Coatings, and any other foreign substances.

Bare/Unfinished Wood must be cleaned with *Storm System 30210 All Surface Cleaner*, fully rinsed, and allowed proper dry time. **Mold & Mildew** should be treated with *Storm System 40210 All Surface Mold & Mildew Stain Remover* and thoroughly rinsed. **Weathered Wood** should be free of all gray/dead wood fibers. This can be achieved by sanding the surface and treating the surface with *Storm System 20410 Wood Restorer*. Use *Storm System 10310 Wood Brightener/Neutralizer* to brighten wood that may darken more than expected, especially cedar and redwood, and to neutralize any remaining cleaner. **Mill Glaze** must be removed from the surface by abrasion or be chemically treated to the point where proper penetration and adhesion of coatings can take place. **Previous Coatings** must be fully removed prior to staining. Proper penetration is required for Storm Stains to reach optimal performance levels. To remove prior coatings, sanding down to bare wood and/or applying *Storm System 50420 Wood Stripper* followed by *Storm System 10310 Wood Brightener/Neutralizer* and an extensive water rinse.

Please Refer to the Technical Data Sheet found @ stormstain.com for full surface preparation instructions.

APPLICATION: Apply only 1 coat of Dual Dispersion Transparent Stain + Sealer. Stir thoroughly. This product is of proper consistency as packaged, to be applied without thinning under normal environmental and application conditions. This product is best applied by synthetic brush, roller, or spray. If spraying or rolling, back brushing is **required** to ensure stain is worked into the wood and evenly distributed. Appearance varies with different species of wood. Samples should be tested on the actual wood being used to ensure an acceptable appearance.

DRYING TIME: To Touch: 4 Hours Light Traffic: 12-24 Hours Full Use: 72 Hours *70°F (21°C) and 50% relative humidity.

CLEANUP: Soap & Water.

COVERAGE RATE: 200-400 SQ. FT. per gal. depending on type of wood, porosity & application method.

LIMITATIONS: Do Not use over previously painted, stained or varnished surfaces unless stripped down to bare wood and properly prepared. Temperatures of both air and surface should be at least 50°F (10°C) during application and drying time. Do not apply in hot sunlight or if wet weather is expected within 48 hours. Surfaces are slippery when wet. Use caution when walking on wet surfaces during application. Do not mix with oil, water or other types of paint or stain. All loose surface wood fibers must be completely removed. Storm System stains provide maximum resistance to fading and mildew.

Made in the USA with Globally Sourced Materials.

PREVIOUS
PACKAGING



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.



150 Dascomb Rd.
Andover, MA
800.225.1141
icpgroup.com