

DEWALT®

**THE MOST
COMPACT
DRYWALL SCREWGUN
IN ITS CLASS****



DCF630 20V MAX* XR® BRUSHLESS DRYWALL SCREWGUN



* Maximum initial battery voltage (measured without a workload) is 20 volts. Nominal voltage is 18.

** Tool only, class defined as Pro-grade cordless drywall screwguns



VARIABLE OPERATION MODES



ELECTRONIC MODE SELECT



COMPACT AND LIGHTWEIGHT

GUARANTEED TOUGH.®

DCF630SS

20V MAX* XR® BRUSHLESS DRYWALL SCREWGUN



SPECIFICATIONS

NO LOAD SPEED	0-3,300/0-4,850 RPM
DRIVE	1/4 in. HEX
PUSHSTART MODE	YES
LOCK-ON MODE	YES
TOOL WEIGHT (TOOL ONLY)	2.2 lbs.
LED	YES
TOOL CONNECT™ SYSTEM CHIP READY™	YES
(Chip Sold Separately)	

TOOL WARRANTY

**3
YEAR**
LIMITED
WARRANTY

**1
YEAR**
FREE
SERVICE

**90
DAY**
MONEY BACK
GUARANTEE

TOOLS AND COMBO KITS

SCREWGUN



DCF630B
(Tool Only)



DCF630D2
(2.0 Ah, 2 Battery Kit)

SCREWGUN & CUT-OUT TOOL



DCK265D2
(2.0 Ah, 2 Battery Kit)

SCREWGUN & IMPACT DRIVER



DCK268P2
(5.0 Ah, 2 Battery Kit)

RELATED PRODUCTS



DCE555

20V MAX* XR® Drywall Cut-Out Tool

Features a 26,00 RPM brushless motor for efficient and consistent cutting of a variety of wall paneling substrates.



DCF887

20V MAX* XR® 1/4 in. 3-Speed Impact Driver

Delivers up to 1,825 in.-lb of torque in a compact design of just 5.3 inches front to back. The multi-speed settings are designed for productivity in a wide variety of applications.



DCF6202

Collated Drywall Screwgun Attachment

Features tool-free screw length, fine-depth adjustments, and tool-free spring removal for easy cleaning. The attachment's 360 degree rotation capability and slim nose with removable shoe allow easy access into tight corners. Compatible with DCF630. (Sold Separately)

*Maximum initial battery voltage (measured without a workload) is 20 volts. Nominal voltage is 18.

Copyright © 2022 DEWALT. The following are trademarks for one or more DEWALT power tools, accessories, anchors and concrete adhesives: The yellow and black color scheme; the "D"-shaped air intake grill; the array of pyramids on the handgrip; the kit box configuration; and the array of lozenge-shaped humps on the surface of the tool

DCF630SS

GUARANTEED TOUGH.®

1-800-4-DEWALT

www.DEWALT.com