ASSEMBLY INSTRUCTION

PATIO DOUBLE LOUNGE



WF300797,WF300798



Note:

- 1. 50% Tighten before fixing all screws, Allen wrench is recommended instead of an electric drill.
- 2. Place the item on a flat ground to adjust and make sure it remains stable.
- 3. Tighten up all screw with tools gradually.
- 4. If screw are not aligned with holes during assembly, please loosen all the other screws to 50% and continue the assembly process.
- 5. If the item is not stable, please loosen all screws, adjust it on a flat ground and tighten up all screws again.
- 6. Note: If one or some screws are fully tighten during assembly, chances are the others will not be aligned with holes. In addition, all the holes are designed to be relatively larger to provide more space for the adjustment of the screws.





Hardware List:			
1 x 4 pcs Extra 2 pcs	(2) x 16 pcs Extra 2 pcs	③ x 20 pcs Extra 2 pcs	④ x 11 pcs Extra 2 pcs
Extra 2 pcs	Extra 2 pcs	Extra 2 pcs	Extra 2 pcs
			$\overline{0}$
BOLT M6 x 20MM	BOLT M6 x 30MM	BOLT M6 x 35MM	BOLT M6 x 55MM
(5) x 76 pcs Extra 5 pcs	6) x 10 pcs Extra 2 pcs	(7) x 21 pcs Extra 2 pcs	(8) x 10 pcs Extra 2 pcs
\bigcirc	\bigcirc		Θ
FLAT WASHER M6	WASHER M6 x 5MM	NUT M6	COVER NUT M6
9 x 1 pc	10 x 2 pcs	(1) x 2 pcs	(12) x 4 pcs
5			Extra 2 pcs
KEY	ALLEN KEY	GASLIFT	SCREW
(13) x 1 pc	(14) x 2 pcs	(15) x 4 pcs	
	Extra 1 pcs	Extra 2 pcs	
SCREW DIVER	WASHER M6 x 10MM	BOLT M6 x 25MM	



Use Allen key to loosen Bolt on the side of Back Left (B) about 10 mm.



Page: 6/20







Connect The Part from Step 7 & Front Bare (K), tighten Bolt (2), Flat Washer (5) with Allen Key (10).







Page: 12/20



Page: 13/20













