Specification	TK1
Folded Size	39.4(L) * 30.3(W) * 29.5(H) in /100(L) * 77(W) * 75(H) cm
Recommended Height	5'-6'3"
Top Tube Horizontal	30 in / 558 mm
Wheelbase	36 in / 913 mm
Stand Over Height	16 in / 407 mm
Handle Bar Length	26 in / 660 mm
Total Length	66 in / 1670 mm
Total Width	29 in / 730 mm
Seat Height	30.3~39 in/770~990 mm
Handle Bar Height	43.7~45.7 in/1110~1160 mm
Front Basket	12.6 * 11.8 * 5.7 in/320 * 300 * 145 mm
Rear Basket	18.9 * 14.2 * 6.3 in/480 * 360 * 160 mm
Wheel Size	20 in
Seat Size	11.8 * 10.6 in /30cm * 27 cm
Weight	G.W. 115.7lbs, N.W. 89.9lbs
Frame	6061 Aluminum+Hiten Steel, Folding Structure, Rear Differential Mechanism
Fork	Suspension, Coil Spring Structure, Mechanical Lockout
Handle Bar	Alloy, BM* Style, Barboe 1.25in, Length 25.98in, Rise 4.72in
Stem	Alloy, Barboe 1.13in * 1.25in, Folding, M*tension Tube 7in
Grip	No information
Saddle	Comfortable Big Vacuum Foaming Seat
Seat Post	Alloy 1.25in * 19.69in Length
Seat Post Clamp	No information
Shifter	No information
Derailleur	No information
Chainwheel	Alloy Crank 6.69in, Steel Chain Ring 36T
Chain	No
Freewheel	18T
Pedal	No information
Display	Multifuctional G51, LCD Gray Screen
Brake	Hydraulic Disc Brake, Alloy, Rotor 7.09in
Brake Level	Alloy 3 Fingers, Hydraulic Disc Brake with Electrical Cut-off Function
Rim	Alloy 20 Inch * 30 * 13G * 36H, AV
Tire	20" * 3.0 CHAOYANG H5183
Spokes	Stainless, 13G
Parking Brake	With
Fenders	With
Rear Rack	With
Assembly	95%
Colors	7 Colors
Carton Size	40in * 29.92in * 29.13in/101.5 * 76 * 74cm
Load Capacity	450 LBS
Motor	48V*500W Peak Power 1000W
Battery	48V*14.5Ah
Range	35~70 Miles
Charger	110-240V 54.6V 2A
Charging Time	6-8 Hours
Max Safe Speed	16 Mph
Controller	Sine Wave FOC 48V 20amp Peak
Pedal Sensor	24 Signals Cadence Sensor
Throttle	Twist Throttle
Wire Harness	Not Water-Resistant
Front Light	Big Led eBike Version with Horn Function
Rear Light	3 Tail Light, Brake Highlight Function & Turn Signals Function