



SUPER PREMIUM

SYNTHETIC BLEND LOWER UNIT 80W90 GEAR LUBE

- Specifically engineered for the Demanding, High Performance Requirements of All Outboard and Stern Drives Requiring 80W90 Gear Oil
- Formulated with Special Pressure Anti-Wear Additives, Superior Lubrication Additives and Corrosion Inhibitors
- Will Not Void Manufacturers' Warranties. Recommended for use in Mercury®, Mercruiser®, Johnson®, Evinrude®, OMC®, Force®, Mariner®, Nissan®, Suzuki®, Yamaha®, Volvo®, Tohatsu®
- Meets Following Specs: API GL-5, API MT-1, SAE J-2360, MACK GO-J

Refer to Manufacturer's Engine Service Manual for flushing and filling instructions. If none are available:

- 1) Remove upper and lower plugs on lower unit gear case and completely drain old oil.
- 2) Install fill tube into lower hole. We recommend using *Star brite Lower Unit Quart Pump* for easy installation.
- 3) Slowly refill unit with new lubricant until fluid appears at the lip of the upper hole.
- 4) Replace upper plug and tighten securely.
- 5) Remove fill tube from lower hole and replace lower plug. Tighten securely.

Please dispose of used oil in accordance with Federal or local laws and regulations.

WARNING: EYE AND SKIN IRRITANT. Contains petroleum distillates. If swallowed, do not induce vomiting. Call a physician immediately. In case of contact with skin, wash thoroughly with soap and water. In case of contact with eyes, flush with fresh water for 15 minutes. Seek professional medical attention. **KEEP OUT OF REACH OF CHILDREN.**

⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.

*All logos, registered trademarks and names are the sole and exclusive property of the respective companies indicated. This product is not connected with or sponsored by any of the named companies.

ASK OUR EXPERTS

www.starbrite.com (800) 327-8583



Star brite® Ft. Lauderdale, FL 33314



Made in U.S.A.

PART: 27232



0 71247 27232 1

27232A2V8