TOTO_®

MW7863056CEFG(A).10

Drake[®] Transitional WASHLET[®]+ S550e Two-Piece Toilet - 1.28 GPF, 10" Rough-In

FEATURES

- Concealed supply connection for seamless installation
- TORNADO FLUSH[®] system, high-efficiency (1.28 GPF/4.8 LPF)
- Transitional style tank ٠
- CEFIONTECT® ceramic glaze minimizes waste from • sticking to porous ceramic surfaces.
- 10" Rough-in, supply line sold separately
- Universal Height •
- Chrome plated trip lever •
- Auto flush available as upgrade •
- Elongated front bowl and WASHLET+ S550e and tank set
- EWATER+® auto-cleans wand and bowl
- On-demand remote function cleans wand with FWATFR+
- PREMIST[®] of bowl before each use
- Remote control operated
- Auto Open / Close lid
- Night light

MODELS

- MW7863056CEFGA.10 (#01) With CEFIONTECT ceramic glaze, WASHLET+ S550e with contemporary design and Auto Flush
- C776CEFGT40.10 Elongated bowl with CEFIONTECT
- **ST786EA**
- Tank and cover only
- SW3056AT40 WASHLET+ S550e
- **THU767**
- Auto Flush Kit
- MW7863056CEFG.10 (#01) Same as MW7863056CEFGA.10 without Auto Flush

OPTIONAL COMPONENTS

THU398(#01, #PN, #BN) Trip Lever - Cotton, Polished Nickel, Brushed Nickel

COLORS/FINISHES

#01 Cotton





UNIVERSAL HEIGHT

PRODUCT SPECIFICATION

The two-piece high-efficiency TORNADO FLUSH toilet shall be 1.28 GPF/4.8 LPF. Universal Height Toilet with CEFIONTECT glaze finish. Toilet shall be 10" rough-in, elongated front bowl and chrome trip lever. Toilet shall be TOTO Model MW7863056CEFG .10#01. See TOTO Specification sheet SW3056AT40 for details on required WASHLET.

CODES/STANDARDS

- Meets and exceeds ASME A112.19.2/CSA B45.1
- Certifications: IAPMO(cUPC®), EPA WaterSense, State of Massachusetts, City of Los Angeles, and others
- Code Compliance: UPC, IPC, NSPC, NPC Canada, and others
- Legislative Compliance: California Green Building Code, City of Los Angeles Water Efficiency Ordinance, and others
- ADA compliant (when installed with trip lever located on the approach side)
- Complies with CA Prop 65 warning requirements



Drake® Transitional WASHLET®+ S550e Two-Piece Toilet - 1.28 GPF, 10" Rough-In

SPECIFICATIONS

| Water Use | 1.28 GPF (4.8 LPF) |
|------------------------|---|
| Flush System | TORNADO FLUSH® |
| Min. Water Pressure | 8 psi (Flowing) |
| Water Surface | 9" x 6-7/8" |
| Trap Diameter | 2-1/8" |
| Rough-in | 10" |
| Trap Seal | 2-1/8" |
| Warranty | One Year Limited Warranty |
| Material | Vitreous China |
| Shipping Weight | C776CEFGT40.10 62 lbs. ST786EA 34 lbs. |
| Shipping Dimensions | C776CEFGT40.10 30-1/8" L× 15-1/4" W1 × 10-7/8" W2 × 17-3/4" H ST786EA 20" L × 9-3/8" W × 15-5/8" H |

See SW3056AT40 Specification Sheet for details on included WASHLET.

INSTALLATION NOTES

Back-to-Back Toilet Installations:

TOTO recommends the use of a nationally listed, double sanitary tee-wye only, in vertical waste stacks, in accordance with the stipulations noted in the majority of nationally recognized plumbing codes.



To maintain adequate wall gap between the back of the tank and wall, mount the floor flange at a nominal 10" rough-in distance.

DIMENSIONS



Ph: (888) 295-8134 | Fax: (800) 699-4889 | www.totousa.com | © TOTO USA

These dimensions and specifications are subject to change without notice