

Model 74B UL Listed Wire Combinations Strip Solid Wire #16 and smaller 7/16 in., all others 3/8 in.

UL File Number E5238

Copper to Copper wire only (do not use on aluminum).

For use with solid or stranded combinations



300 Volt Maximum	600 Volt Maximum	
1 #10 w/2 #12	1 #8	1 #14 w/1 to 4 #16, #18 or #20
	1 #10	1 #14 w/1 #16 w/1 to 3 #20
	1 to 3 #12	1 #14 w/1 #18 w/1 to 3 #20
	1 to 4 #14	2 #14 w/1 to 3 #16, #18 or #20
	2 to 5 #16	2 #14 w/1 #16 w/1 or 2 #18 or #20
	2 to 5 #18	2 #14 w/1 #16 w/1 to 3 #22
	3 to 6 #20	3 #14 w/1 #16 w/1 #18, #20 or #22
	1 #10 w/1 #12	3 #14 w/1 #18 w/1 #20 or #22
	1 #10 w/1 or 2 #14, #16 or #18	3 #14 w/1 or 2 #16
	1 #10 w/3 or 4 #16 or #18	3 #14 w/1 or 2 #18 or #20
	1 #10 w/1 #12 w/1 #14 or #16	4 #14 w/1 #16 or #18
	1 #10 w/1 #12 w/1 or 2 #18	1 #16 w/1 #18 w/2 or 3 #20 or #22
	1 #10 w/1 #14 w/2 #16	1 #16 w/1 #18 w/3 or 4 #22
	1 #10 w/1 #14 w/1 to 3 #18	1 #16 w/2 #20 w/2 #22
	1 #10 w/2 #14 w/1 #16	1 #16 w/1 to 4 #18, #20 or #22
	1 #10 w/1 #16 w/1 or 2 #18	2 #16 w/1 to 3 #18, #20 or #22
	1 #12 w/1 to 3 #14, #16 or #18	2 #16 w/1 #18 w/1 or 2 #20 or #22
	1 #12 w/4 #16 or #18	3 #16 w/1 or 2 #18, #20 or #22
	1 #12 w/1 #14 w/3 #16	3 #16 w/1 #18 w/1 #20 or #22
	1 #12 w/2 #14 w/2 #16	4 #16 w/1 or 2 #18, #20 or #22
	2 #12 w/1 or 2 #14	1 #18 w/3 or 4 #20 or #22
	2 #12 w/1 or 2 #16 or #18	1 #18 w/2 #20 w/3 #22
	2 #12 w/1 #14 w/1 #16 or #18	2 #18 w/3 #20 or #22
	2 #12 w/1 #16 w/1 or 2 #18	2 #18 w/1 #20 w/3 #22