



STORE+®

48" x 34" Vikrell® shower with Aging in Place backerboards, center drain

72320106



Features

- 3-1/8" (79 mm) threshold
- Durable high-gloss finish
- Three-piece tongue-and-groove walls with snap-together installation
- Includes four rimmed shelves, two large bins, two shower hooks and two soap dishes with towel bars; shaving ledge/footrest
- Aging in Place backerboards

Material

- Made from solid Vikrell® material for strength, durability, and lasting beauty

Installation

- Alcove
- Center drain
- Caulk-free installation

Recommended Products/Accessories

1500D-48 Framed pivot shower door
5475-48 Frameless sliding shower door
5970-48 Framed sliding shower door
5975-48 Framed sliding shower door
5976-48 Framed sliding shower door
547808-48 Frameless sliding shower door
581075-48 Frameless sliding shower door
80001012 12" straight grab bar
80001018 18" straight grab bar
80001024 24" straight grab bar
72186104 Freestanding shower seat
K-23726 Drain treatment
K-23733 Vikrell® cleaner

Included Components

72321100 48" x 34" Vikrell® shower base, center drain
72322106 48" Vikrell® shower back wall with Aging in Place backerboards
72305106 34" Vikrell® shower end wall set with Aging in Place backerboards



Codes/Standards

CSA B45.5/IAPMO Z124
ASTM E162
ASTM E662
HUD, UM Bulletin 73
IAPMO Certification


STERLING® Vikrell® or Acrylic Baths and Shower Bases Ten-Year Limited Warranty


See website for detailed warranty information.

Available Colors/Finishes

Color tiles intended for reference only.

Color	Code	Description
-------	------	-------------

	0	White
---	---	-------



Technical Information

All product dimensions are nominal.

Drain location:	Center
Basin area, bottom:	29-1/16" x 44-3/4" (739 mm x 1137 mm)
Basin area, top:	29-1/16" x 44-3/4" (739 mm x 1137 mm)
Weight:	114 lbs (51.7 kg)
Minimum flat for door:	2-1/2" (64 mm)
Maximum door height:	72-1/2" (1842 mm)
Maximum door width:	44-3/4" (1137 mm)

Notes

Install this product according to the installation instructions.

Studs should be positioned roughly as shown. Double studding is recommended for pivot shower door installations.

Attach grab bars at the specified backer board locations only.