

STP-PC

Product Specs

Construction

Durable stamped aluminum construction with powder coat finish
 High efficiency, fully sealed, maintenance-free LED chamber
 Gasketed faceplate protects from elements

Electrical

Operating temperature rating of -10°F to 122°F (-23°C to 50°C)
 Input voltage of 120V
 TM-21 Projected L70(6k) life 50,000 hours
 LM-79, LM-80 testing performed in accordance with IESNA standards

Finish

White with powder coat finish
 Also available in Black and Oil-rubbed bronze.
 Faceplate is paintable to match any design space

Installation

Mounts directly in standard single-gang junction boxes
 Design allows fixture to be mounted in horizontal or vertical orientation
 Wet location rated for indoor and outdoor use

Warranty

5-year limited system warranty standard



FINISH OPTIONS

BK



OB



PRODUCT INFORMATION

Product Specs	STP-PC
LED Lifetime Projected:	50,000 hours
Power Draw:	1W
Input Voltage :	120V
Trim Height:	4.5 in (114 mm)
Trim Width:	2.75 in (70 mm)

ORDERING INFORMATION

Example: STP-10-120-WH-PC

Series	Version	Voltage (V)	Faceplate Color	Photocell
STP	10	120V	WH (White)	PC

FACEPLATE ORDERING INFORMATION (PC)

Part Number	Description
FPHBK-PC	Horizontal Black
FPVBK-PC	Vertical Black
FPHOB-PC	Horizontal Oil-rubbed Bronze
FPVOB-PC	Vertical Oil-rubbed Bronze
FPHWH-PC	Horizontal White



NOTE: Each STP | STP-PC ships standard with one white vertical faceplate. Optional faceplates must be ordered separately.